

Package ‘XhybCasneuf’

June 12, 2025

Version 1.46.0
Date 2007-06-21
Title EBI/PSB cross-hybridisation study package
Author Tineke Casneuf <tine@ebi.ac.uk>
Maintainer Tineke Casneuf <tine@ebi.ac.uk>
Depends R (>= 2.4.0), affy , ath1121501cdf , tinesath1cdf ,
RColorBrewer , methods, grid
Description Cross-hybridisation study on the ATH1 Affymetrix GeneChip
License Artistic-2.0
biocViews ExperimentData, Tissue, MicroarrayData, TissueMicroarrayData
git_url <https://git.bioconductor.org/packages/XhybCasneuf>
git_branch RELEASE_3_21
git_last_commit abef7e0
git_last_commit_date 2025-04-15
Repository Bioconductor 3.21
Date/Publication 2025-06-12

Contents

AffysTissue	2
CustomsTissue	3
ex1	4
runSimulation	4
XhybExamples-class	5
Index	7

AffysTissue

Affymetrix' CDF probe set pairs

Description

Affymetrix' CDF probe set pairs

Usage

```
data(AffysTissue)
data(AffysTissueMC)
data(AffysTissue.noBl)
```

Format

These three data.frames contain data for Affymetrix' CDF's probe set pairs with $Q75 \geq 55$. The `pr` and `target` columns hold the names of probe set X and Y, respectively. Column `alSum` contains the $Q75$ value of the alignment scores of X's reporters to the transcript of Y. The `meant2hit` and `PSofTarget` columns contain respectively the gene locus the probe set was designed to target and the probe set ID of the off-target Y, according to Affymetrix (extracted from `ATH1-121501\_annot.csv`). The `peCC` column holds the pairs' Pearson correlation coefficient calculated on their expression intensities in the Tissue dataset (data originally from AtgenExpress Project).

`AffysTissue` is data.frame that contains all Affymetrix' CDF's probe set pairs with $Q75 \geq 55$. `AffysTissueMC` holds a subset of the pairs in `AffysTissue`, namely those whose metacorrelation coefficient is not NA are included. For `AffysTissue.noBl`, the pairs of `AffysTissue` that align to each other with BLAST in at least one direction with an E-value smaller than 10^{-10} were omitted.

Author(s)

Tineke Casneuf <tine@ebi.ac.uk>

References

Casneuf, Van de Peer and Huber, AtgenExpress data used: Schmid, M., Davison, T. S., Henz, S. R., Pape, U. J., Demar, M., Vingron, M. Schoelkopf, B. Weigel, D., and Lohmann, J. (2005) A gene expression map of Arabidopsis development. *Nature Genetics*, 37, 501-506.

See Also

[CustomsTissue](#)

Examples

```
data(AffysTissue)
data(AffysTissueMC)
data(AffysTissue.noBl)

## see also the vignette
```

CustomsTissue	<i>Custom-made CDF's probe set pairs</i>
---------------	--

Description

Custom-made CDF's probe set pairs

Usage

```
data(CustomsTissue)
data(CustomsTissueMC)
data(CustomsTissue.noBl)
```

Format

These three data.frames contain data for the custom-made CDF's probe set pairs with $Q75 \geq 55$. The `pr` and `target` columns hold the names of probe set X and Y, respectively. Column `alSum` contains the $Q75$ value of the alignment scores of X's reporters to the transcript of Y. The `peCC` column holds the pairs' Pearson correlation coefficient calculated on their expression intensities in the Tissue dataset (data originally from AtgenExpress Project).

`CustomsTissue` is data.frame that contains all custom-made CDF's probe set pairs with $Q75 \geq 55$. `CustomsTissueMC` holds a subset of the pairs in `CustomsTissue`, namely those whose metacorrelation coefficient is not NA are included. For `CustomsTissue.noBl`, the pairs of `CustomsTissue` that align to each other with BLAST in at least one direction with an E-value smaller than 10^{-10} were omitted.

Author(s)

Tineke Casneuf <tine@ebi.c.uk>

References

Casneuf, Van de Peer and Huber, AtgenExpress data used: Schmid, M., Davison, T. S., Henz, S. R., Pape, U. J., Demar, M., Vingron, M. Schoelkopf, B. Weigel, D., and Lohmann, J. (2005) A gene expression map of Arabidopsis development. *Nature Genetics*, 37, 501-506.

See Also

[AffysTissue](#)

Examples

```
data(CustomsTissue)
data(CustomsTissueMC)
data(CustomsTissue.noBl)

## see also the vignette
```

ex1

Cross-hybridisation example

Description

Cross-hybridisation example

Usage

```
data(ex1)
data(ex2)
data(ex3)
```

Format

These objects contain the data of three examples of cross-hybridisation.

Author(s)

Tineke Casneuf <tine@ebi.ac.uk>

References

Casneuf, Van de Peer and Huber. Submitted.

Examples

```
data(ex1)
data(ex2)
data(ex3)

plotExample(ex1)
plotExample(ex2)
plotExample(ex3)

## see also the vignette
```

runSimulation*Cross-hybridisation simulation*

Description

Cross-hybridisation simulation

Usage

```
runSimulation()
```

Format

runSimulation is a function that will run the simulation we ran for our study. By modifying the parameters, users can play with it themselves.

Author(s)

Tineke Casneuf <tine@ebi.ac.uk>

References

Casneuf, Van de Peer and Huber (Submitted).

Examples

```
runSimulation()

## see also the vignette
```

XhybExamples-class	<i>Class "XhybExamples"</i>
--------------------	-----------------------------

Description

Class containing information of cross-hybridisation examples

Objects from the Class

Objects can be created by calls of the form `new("XhybExamples", ...)`.

Slots

X: Object of class "character" contains the ID of probe set X
Y: Object of class "character" contains the ID of probe set Y
IVX: Object of class "numeric" contains the expression intensities of X in the Tissue dataset
IVY: Object of class "numeric" contains the expression intensities of Y in the Tissue dataset
IVXi: Object of class "matrix" contains the expression intensities of X's reporters in the Tissue dataset
ai: Object of class "numeric" contains the alignment scores of X's reporters to Y's transcript sequence

Methods

```
plotExample signature(ex = "XhybExamples"): ...
```

Author(s)

Tineke Casneuf <tine@ebi.ac.uk>

References

Casneuf, Van de Peer and Huber (submitted); AtgenExpress data used: Schmid, M., Davison, T. S., Henz, S. R., Pape, U. J., Demar, M., Vingron, M. Schoelkopf, B. Weigel, D., and Lohmann, J. (2005) A gene expression map of Arabidopsis development. Nature Genetics, 37, 501-506.

Examples

```
data(ex1)
data(ex2)
data(ex3)
plotExample(ex1)
plotExample(ex2)
plotExample(ex3)
```

Index

- * **classes**
 - XhybExamples-class, [5](#)
- * **datasets**
 - AffysTissue, [2](#)
 - CustomsTissue, [3](#)
 - ex1, [4](#)
- * **manip**
 - runSimulation, [4](#)

AffysTissue, [2](#), [3](#)
AffysTissueMC (AffysTissue), [2](#)

CustomsTissue, [2](#), [3](#)
CustomsTissueMC (CustomsTissue), [3](#)

ex1, [4](#)
ex2 (ex1), [4](#)
ex3 (ex1), [4](#)

plotExample (XhybExamples-class), [5](#)
plotExample, XhybExamples-method
(XhybExamples-class), [5](#)

runSimulation, [4](#)

XhybExamples-class, [5](#)