

# Package ‘HiSpaR’

April 23, 2026

**Type** Package

**Title** Hierarchical Inference of Spatial Positions from Hi-C Data

**Version** 0.99.6

**Date** 2026-01-15

**Description** Provides R bindings for HiSpa, a hierarchical Bayesian model for inferring three-dimensional chromatin structures from Hi-C contact matrices using Markov Chain Monte Carlo (MCMC) sampling. The package implements a cluster-based hierarchical approach that efficiently handles large-scale Hi-C datasets. It uses Rcpp and RcppArmadillo for efficient C++ integration with the original HiSpa C++ implementation, enabling fast computation of chromatin structure inference through parallel MCMC sampling.

**License** MIT + file LICENSE

**Depends** R (>= 4.5.0)

**Imports** Rcpp (>= 1.0.0), utils, stats, Matrix, HiCExperiment

**biocViews** Software, Epigenetics, HiC, StructuralPrediction, Bayesian, Spatial

**LinkingTo** Rcpp, RcppArmadillo

**SystemRequirements** C++17, GNU make, Armadillo (>= 9.0), OpenMP

**URL** <https://github.com/masterStormtrooper/HiSpaR>

**BugReports** <https://github.com/masterStormtrooper/HiSpaR/issues>

**Encoding** UTF-8

**LazyData** false

**RoxygenNote** 7.3.3

**Suggests** testthat (>= 3.0.0), knitr, rmarkdown, BiocStyle, rgl, HiContactsData, HiContacts, plotly, callr

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/HiSpaR>

**git\_branch** devel

**git\_last\_commit** de0d420

**git\_last\_commit\_date** 2026-03-26  
**Repository** Bioconductor 3.23  
**Date/Publication** 2026-04-22  
**Author** Yingcheng Luo [aut, cre]  
**Maintainer** Yingcheng Luo <lyc22@mails.tsinghua.edu.cn>

## Contents

HiSpaR-package . . . . .	2
hispa_analyze . . . . .	3
su1_contact_mat . . . . .	5
<b>Index</b>	<b>7</b>

---

HiSpaR-package	<i>HiSpaR: Hierarchical Inference of Spatial Positions from Hi-C Data</i>
----------------	---

---

## Description

HiSpaR provides R bindings for the HiSpa C++ library, enabling hierarchical Bayesian inference of 3D chromatin structures from Hi-C contact matrices.

## Details

The package provides functions to:

- Analyze Hi-C contact matrices using MCMC sampling
- Infer 3D chromatin structures
- Use prior information from other datasets
- Perform cluster-based hierarchical analysis

Main functions:

- [hispa\\_analyze](#): Run complete HiSpa analysis

## Author(s)

**Maintainer:** Yingcheng Luo <lyc22@mails.tsinghua.edu.cn>

## See Also

Useful links:

- <https://github.com/masterStormtrooper/HiSpa>
- Report bugs at <https://github.com/masterStormtrooper/HiSpa/issues>

---

hispa\_analyze

*Run HiSpa MCMC Analysis*


---

## Description

Performs hierarchical Bayesian inference of 3D chromatin structure from Hi-C contact matrix using MCMC sampling. This function follows the exact workflow from the HiSpa C++ implementation.

## Usage

```
hispa_analyze(
  hic_experiment,
  output_dir,
  mcmc_iterations = 6000L,
  num_clusters = 0L,
  mcmc_burn_in = 0L,
  mcmc_initial_sd = 0.1,
  mcmc_sd_floor = 1e-04,
  mcmc_sd_ceil = 0.3,
  use_cluster_init = FALSE,
  cluster_init_iterations = 1000L,
  cluster_initial_sd = 0.1,
  save_samples = FALSE,
  sample_interval = 50L,
  verbose = TRUE,
  filter_quantile = -1,
  safe_mode = TRUE
)
```

## Arguments

hic_experiment	A Bioconductor 'HiCExperiment' object or a numeric matrix containing Hi-C contact data. If a 'HiCExperiment' object, the function extracts the contact matrix using 'gi2cm()' from the interactions and converts it to a numeric matrix for analysis. If a matrix, it is used directly.
output_dir	Character string specifying the output directory path.
mcmc_iterations	Integer, number of MCMC iterations (default: 6000).
num_clusters	Integer, number of clusters for hierarchical analysis. If 0 (default), automatically determined as sqrt(n).
mcmc_burn_in	Integer, number of burn-in iterations to discard (default: 0).
mcmc_initial_sd	Numeric, initial standard deviation for MCMC proposals (default: 0.1).
mcmc_sd_floor	Numeric, minimum allowed standard deviation (default: 0.0001).
mcmc_sd_ceil	Numeric, maximum allowed standard deviation (default: 0.3).

<code>use_cluster_init</code>	Logical, use cluster-based initialization instead of random initialization (default: FALSE).
<code>cluster_init_iterations</code>	Integer, number of iterations for cluster initialization MCMC (default: 1000).
<code>cluster_initial_sd</code>	Numeric, initial standard deviation for cluster initialization MCMC (default: 0.1).
<code>save_samples</code>	Logical, whether to save MCMC trace samples (default: FALSE).
<code>sample_interval</code>	Integer, save samples every n iterations (default: 50).
<code>verbose</code>	Logical, enable verbose output (default: TRUE).
<code>filter_quantile</code>	Numeric, quantile threshold for filtering loci by contact counts (default: -1, no filtering). If $\geq 0$ , loci with row sums below this quantile are removed. For example, 0.1 removes loci in the bottom 10% of contact counts.
<code>safe_mode</code>	Logical, whether to run analysis in a safe subprocess using callr (default: TRUE). If TRUE and callr is available, analysis runs in an isolated subprocess to prevent R crashes from affecting the parent session. Set to FALSE to run inline.

## Details

This function implements the complete HiSpa workflow:

1. Filter loci by contact count (optional)
2. Load contact matrix from file
3. Assign loci to clusters (k-means)
4. Build cluster relationships
5. Initialize structure (random or cluster-based)
6. Assemble global structure
7. Run main MCMC algorithm
8. Save results to output directory

**Locus Filtering:** By default, no filtering is applied (`filter_quantile = -1`). If `filter_quantile`  $\geq 0$ , loci with contact counts below the specified quantile are removed before analysis. For example, `filter_quantile = 0.1` removes loci in the bottom 10% of contact counts. This improves computational efficiency and focuses analysis on loci with sufficient data.

All results are automatically saved to the output directory:

- **final\_positions.txt** - Final inferred 3D coordinates (n x 3 matrix)
- **initial\_positions.txt** - Initial positions before MCMC (n x 3 matrix)

Read results using standard R functions: `final_pos <- read.table("output_dir/final_positions.txt")`

**Value**

A list containing:

- **positions** - A numeric matrix of dimensions  $n \times 3$  containing the final inferred 3D coordinates of loci. Rows correspond to loci, columns are (x, y, z).
- **beta0** - The final intercept parameter of the log-distance relationship.
- **beta1** - The final slope parameter of the log-distance relationship.

If filtering was applied, the positions matrix has an attribute 'filtered\_locus\_indices' containing the original indices of the retained loci (before filtering). Additionally, all analysis results are saved as text files in the output directory.

**Examples**

```
# Load example contact matrix
data(su1_contact_mat)

# Check dimensions
dim(su1_contact_mat)

# Example 1: Run analysis with matrix input
su_res <- hispa_analyze(
  hic_experiment = su1_contact_mat,
  output_dir = tempdir(),
  mcmc_iterations = 100,
  mcmc_burn_in = 10,
  use_cluster_init = FALSE,
  verbose = TRUE
)

# check results
dim(su_res$positions) # Should be n x 3
```

---

su1_contact_mat	<i>Example Hi-C Contact Matrix</i>
-----------------	------------------------------------

---

**Description**

Hi-C contact matrix of Human Chromosome 21, collected from <https://zenodo.org/records/3928890>. This dataset is provided as an example for testing and demonstrating the HiSpaR package functionality.

**Usage**

```
su1_contact_mat
```

**Format**

A symmetric numeric matrix with 649 rows and 649 columns, where entry (i,j) represents the normalized contact frequency between genomic loci i and j. The matrix is:

**Dimensions** 649 x 649

**Type** Numeric matrix

**Symmetry** Symmetric (contact\_matrix[i,j] = contact\_matrix[j,i])

**Diagonal** Zero or near-zero (self-contacts)

**Range** Non-negative contact frequencies

**Details**

This contact matrix represents chromatin interaction frequencies derived from Hi-C experiments on Human Chromosome 21. Higher values indicate more frequent spatial proximity between genomic loci in the 3D nuclear space.

The data can be used directly with [hispa\\_analyze](#)

**Source**

Human Hi-C data, chromosome 21, collected from <https://zenodo.org/records/3928890>

**See Also**

[hispa\\_analyze](#) for running the analysis

**Examples**

```
# Load the example data
data(su1_contact_mat)

# Check dimensions
dim(su1_contact_mat)

# Check if matrix is symmetric
isSymmetric(su1_contact_mat)

# Summary statistics
summary(as.vector(su1_contact_mat))

# Visualize contact matrix
image(su1_contact_mat,
      main = "Hi-C Contact Matrix (SU1)",
      xlab = "Genomic Locus",
      ylab = "Genomic Locus")
```

# Index

\* **datasets**

su1\_contact\_mat, [5](#)

\* **internal**

HiSpaR-package, [2](#)

hispa\_analyze, [2](#), [3](#), [6](#)

HiSpaR (HiSpaR-package), [2](#)

HiSpaR-package, [2](#)

su1\_contact\_mat, [5](#)