

# Package ‘CSOA’

May 1, 2026

**Type** Package

**Title** Calculate per-cell gene signature scores in scRNA-seq data using cell set overlaps

**Version** 1.3.0

**Description** Cell Set Overlap Analysis (CSOA) is a tool for calculating per-cell gene signature scores in an scRNA-seq dataset. CSOA constructs a set for each gene in the signature, consisting of the cells that highly express the gene. Next, all overlaps of pairs of cell sets are computed, ranked, filtered and scored. The CSOA per-cell score is calculated by summing up all products of the overlap scores and the min-max-normalized expression of the two involved genes. CSOA can run on a Seurat object, a SingleCellExperiment object, a matrix and a dgCMatrix.

**License** MIT + file LICENSE

**Imports** dplyr, ggplot2, henna, kerntools, methods, paletteer, qs2, reshape2, rlang, Seurat, SeuratObject, SummarizedExperiment, spatstat.utils, stats, textshape

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Suggests** BiocStyle, knitr, patchwork, rmarkdown, scRNAseq, scuttle, stringr, testthat (>= 3.0.0)

**biocViews** Software, SingleCell, GeneSetEnrichment, GeneExpression

**VignetteBuilder** knitr

**URL** <https://github.com/andrei-stoica26/CSOA>

**BugReports** <https://github.com/andrei-stoica26/CSOA/issues>

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/CSOA>

**git\_branch** devel

**git\_last\_commit** d3d3e07

**git\_last\_commit\_date** 2026-04-28

**Repository** Bioconductor 3.24

**Date/Publication** 2026-05-01

**Author** Andrei-Florian Stoica [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-5253-0826>>)

**Maintainer** Andrei-Florian Stoica <[andreistoica@foxmail.com](mailto:andreistoica@foxmail.com)>

## Contents

CSOA-package . . . . .	2
attachCellScores.default . . . . .	3
basicHeatmap . . . . .	4
breakWeakTies . . . . .	5
cellDistribution . . . . .	6
cellSetsOverlaps . . . . .	6
computePairScores . . . . .	7
computePCPairScores . . . . .	8
edgeLists.default . . . . .	8
expMat . . . . .	9
featureWes . . . . .	10
geneRadialPlot . . . . .	11
generateOverlaps . . . . .	12
getPairs . . . . .	13
networkPlotDF . . . . .	13
overlapCutoffPlot . . . . .	14
overlapGenes . . . . .	15
overlapNetworkPlot . . . . .	16
overlapPairs . . . . .	17
percentileSets . . . . .	17
prefilterOverlaps . . . . .	18
processOverlaps . . . . .	18
qGrab . . . . .	19
runCSOA . . . . .	20
scoreCells . . . . .	21
scoreCellsCore . . . . .	23
scoreModules . . . . .	24
<b>Index</b>	<b>25</b>

---

CSOA-package	<i>CSOA: Calculate per-cell gene signature scores in scRNA-seq data using cell set overlaps</i>
--------------	---

---

## Description

Cell Set Overlap Analysis (CSOA) is a tool for calculating per-cell gene signature scores in an scRNA-seq dataset. CSOA constructs a set for each gene in the signature, consisting of the cells that highly express the gene. Next, all overlaps of pairs of cell sets are computed, ranked, filtered and scored. The CSOA per-cell score is calculated by summing up all products of the overlap scores and the min-max-normalized expression of the two involved genes. CSOA can run on a Seurat object, a SingleCellExperiment object, a matrix and a dgCMatix.

## Author(s)

**Maintainer:** Andrei-Florian Stoica <andreistoica@foxmail.com> ([ORCID](#))

## See Also

Useful links:

- <https://github.com/andrei-stoica26/CSOA>
- Report bugs at <https://github.com/andrei-stoica26/CSOA/issues>

---

attachCellScores.default

*Attach CSOA scores to object*

---

## Description

This function attaches the data frame of CSOA scores to the input object.

## Usage

```
## Default S3 method:
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'Seurat'
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'SingleCellExperiment'
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'matrix'
attachCellScores(scObj, scoreDF, ...)

## S3 method for class 'dgCMatrx'
attachCellScores(scObj, scoreDF, ...)

attachCellScores(scObj, ...)
```

## Arguments

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
scoreDF	Data frame of CSOA scores.
...	Additional arguments.

## Details

If the input object is of the Seurat or SingleCellExpression class, it will be returned with added CSOA scores. Otherwise, a list containing the expression matrix and the CSOA scores data frame will be returned.

## Value

A Seurat object with CSOA scores added to metadata.  
A SingleCellExperiment object with CSOA scores added to colData.  
A list containing the expression matrix and the CSOA scores data frame.  
A list containing the expression matrix and the CSOA scores data frame.

**Examples**

```
library(Seurat)
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- sample(20, 8000, TRUE)
seuratObj <- CreateSeuratObject(mat)
seuratObj <- NormalizeData(seuratObj)
scores <- data.frame(CSOA = runif(300))
seuratObj <- attachCellScores(seuratObj, scores)
head(seuratObj$CSOA)
```

---

basicHeatmap

*Plot a simple heatmap*


---

**Description**

This function plots a simple heatmap, with clustering but no dendograms.

**Usage**

```
basicHeatmap(
  mat,
  aesNames = c("x", "y", "Score"),
  title = "Heatmap",
  axisTextSize = 7,
  palette = paletteer_c("grDevices::Plasma", 30),
  ...
)
```

**Arguments**

mat	A matrix.
aesNames	A character vector of length 3 representing the y, x and fill aes elements.
title	Plot title.
axisTextSize	Axis text size.
palette	Color palette.
...	Other arguments passed to <code>henna::centerTitle</code> .

**Value**

A ggplot object.

**Examples**

```
mat <- matrix(0, 10, 20)
mat[sample(length(mat), 50)] <- runif(50, max = 2.5)
basicHeatmap(mat)
```

---

breakWeakTies	<i>Remove overlap pairs with low Jaccard scores</i>
---------------	---

---

### Description

This function iteratively removes all overlap pairs with neighbor Jaccard score below a fixed cutoff until no overlap pairs can be removed. Subsequently, overlap ranks are recalculated.

### Usage

```
breakWeakTies(  
  overlapDF,  
  cutoff = 1/3,  
  doConnComp = FALSE,  
  mtMethod = c("BY", "BH")  
)
```

### Arguments

overlapDF	An overlap data frame.
cutoff	A cutoff used in the filtering of edges with low Jaccard scores.
doConnComp	Whether to calculate the connected components.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH'). Default is 'BY'.

### Details

The functions removes overlaps for which the two involved genes record too few shared neighbors—genes whose cell set significantly overlaps with those of both overlap genes.

### Value

An overlap data frame in which edges with low Jaccard scores have been removed.

### Examples

```
overlapDF <- data.frame(gene1=paste0('G', c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),  
  gene2=paste0('G', c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),  
  ratio=runif(10, 2, 10),  
  pval=runif(10, 0, 1e-10))  
breakWeakTies(overlapDF, cutoff=0.1)
```

---

cellDistribution      *Show the distribution of cell sets among cells*

---

### Description

This function returns a logical matrix that shows the representation of cell sets among all cells.

### Usage

```
cellDistribution(cellSets, allCells)
```

### Arguments

cellSets            A list of character vectors.  
allCells            Names of all cells in the dataset.

### Value

A logical matrix with genes as rows and cells as columns.

### Examples

```
cellSets <- list(c('A', 'H', 'J'),
c('B', 'D', 'E', 'F', 'J'),
c('C', 'I', 'L'))
allCells <- LETTERS[seq(15)]
cellDistribution(cellSets, allCells)
```

---

cellSetsOverlaps      *Calculates the significance of overlaps of pairs of cells sets*

---

### Description

This function computes the statistical significance of overlaps of pairs of cell sets.

### Usage

```
cellSetsOverlaps(cellSets, nCells, pairs = NULL, overlapFileName = NULL)
```

### Arguments

cellSets            A list of character arrays.  
nCells            The total number of cells in the Seurat object.  
pairs            Pairs of cell sets to be assessed. If NULL (as default), all pairs will be assessed.  
overlapFileName    The name of the file where the overlap data frame will be saved. This option can be used to save time when performing exploratory analyses such as trying different jaccardCutoff parameters in breakWeakTies. Default is NULL (the overlap data frame will not be saved).

**Value**

A data frame listing statistics for all cell set overlaps: cell set sizes, recorded and expected shared cells, the recorded-over-expected ratio and the hypergeometric p-value.

**Examples**

```
cellSets <- list(G1 = c('A', 'H', 'J'),
                G2 = c('B', 'D', 'E', 'F', 'J'),
                G3 = c('C', 'I', 'L'))
cellSetsOverlaps(cellSets, 40)
```

---

computePairScores	<i>Compute aggregate gene pair scores</i>
-------------------	---

---

**Description**

This function assesses the relative contribution of each gene pair to the CSOA score

**Usage**

```
computePairScores(
  overlapDF,
  pcPairScores,
  pairFileName = "pairs",
  keepOverlapOrder = FALSE
)
```

**Arguments**

**overlapDF** An overlap data frame.

**pcPairScores** A data frame of pair scores in each cell for each pair in the overlap data frame.

**pairFileName** The name of the file where the pair data frame will be saved.

**keepOverlapOrder** Whether to keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order.

**Value**

A data frame with overlap and pair scores and ranks.

---

computePCPairScores     *Compute per-cell gene pair scores*

---

### Description

This function scores each gene pair corresponding to a top overlap in each cell.

### Usage

```
computePCPairScores(overlapDF, normExp)
```

### Arguments

overlapDF     An overlap data frame.  
normExp     A min-max-normalized expression matrix of the genes involved in top overlaps.

### Details

The score is calculated by multiplying the overlap score with the min-max-normalized expression of the two corresponding genes.

### Value

A data frame with gene pairs as rows and cells as columns.

---

edgeLists.default     *Extract the edge list from overlap data frame or list of overlap data frames*

---

### Description

This function creates a list of data frames with three columns: gene1, gene2 and group. If overlapObj is an overlap data frame, the groups correspond to the connected components. If it is a list of overlap data frames, the groups must be specified as groupNames.

### Usage

```
## Default S3 method:
edgeLists(overlapObj, ...)

## S3 method for class 'data.frame'
edgeLists(overlapObj, ...)

## S3 method for class 'list'
edgeLists(overlapObj, groupNames, cutoff = NULL, ...)

edgeLists(overlapObj, ...)
```

**Arguments**

overlapObj	An overlap data frame or list of overlap data frames.
...	Additional arguments.
groupNames	Names of groups. If provided, must be a vector of the same length as the list of overlap data frames.
cutoff	Number of retained edges from each overlap data frame after refiltering. If NULL (as default), no refiltering will be performed.

**Value**

A list of data frames.

---

expMat	<i>Extracts the data expression matrix from object</i>
--------	--

---

**Description**

This function extracts the data expression matrix from object as a non-sparse matrix. Selected genes can be specified as input.

**Usage**

```
expMat(scObj, ...)

## Default S3 method:
expMat(scObj, genes = NULL, ...)

## S3 method for class 'Seurat'
expMat(scObj, ...)

## S3 method for class 'SingleCellExperiment'
expMat(scObj, ...)

## S3 method for class 'dgMatrix'
expMat(scObj, ...)

## S3 method for class 'matrix'
expMat(scObj, ...)
```

**Arguments**

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
...	Additional arguments.
genes	Genes retained in the expression matrix. If NULL, all genes will be retained

**Value**

An expression matrix.

**Examples**

```
library(Seurat)
mat <- matrix(0, 6, 4)
mat[sample(length(mat), 7)] <- sample(3, 7, TRUE)
seuratObj <- CreateSeuratObject(counts = mat)
seuratObj <- NormalizeData(seuratObj)
expMat(seuratObj)
```

---

featureWes

*A feature plot with a more distinctive color scheme.*


---

**Description**

This function customizes the appearance of `Seurat::FeaturePlot` for improved distinctiveness and aesthetics.

**Usage**

```
featureWes(
  seuratObj,
  feature,
  title = feature,
  idClass = NULL,
  labelSize = 3.5,
  titleSize = 12,
  palette = paletteer_d("wesanderson::Royal1")[c(3, 2)],
  ...
)
```

**Arguments**

<code>seuratObj</code>	A Seurat object.
<code>feature</code>	Seurat feature.
<code>title</code>	Plot title.
<code>idClass</code>	Column to be used for labelling. If <code>NULL</code> , no column-based labels will be generated.
<code>labelSize</code>	Size of labels. Ignored if <code>idClass</code> is <code>NULL</code> .
<code>titleSize</code>	Title size.
<code>palette</code>	Color palette.
<code>...</code>	Additional arguments passed to <code>Seurat::FeaturePlot</code> .

**Value**

A ggplot object.

**Examples**

```

library(Seurat)
mat <- matrix(0, 3000, 800)
mat[sample(length(mat), 90000)] <- sample(8, 90000, TRUE)
seuratObj <- CreateSeuratObject(counts = mat)
seuratObj <- FindVariableFeatures(seuratObj, nfeatures=200)
seuratObj <- NormalizeData(seuratObj)
seuratObj <- ScaleData(seuratObj)
seuratObj <- RunPCA(seuratObj, verbose=FALSE)
seuratObj <- RunUMAP(seuratObj, dims=1:20, verbose=FALSE)
featureWes(seuratObj, 'Feature3')

```

---

geneRadialPlot

*Radial plot for an overlap data frame*


---

**Description**

This function draws a radial plot for an overlap data frame to illustrate gene participation in top overlaps.

**Usage**

```

geneRadialPlot(
  overlapObj,
  title = "Top overlap genes plot",
  degreeLegendTitle = "Number of top overlaps",
  groupLegendTitle = "Group",
  extraCircles = 2,
  groupNames = NULL,
  cutoff = NULL,
  ...
)

```

**Arguments**

overlapObj	An overlap data frame or list of overlap data frames.
title	Plot title.
degreeLegendTitle	The title of the degree legend.
groupLegendTitle	The title of the group legend. If NULL, no groups will be distinguished.
extraCircles	Number of extra circles to be displayed on the plot.
groupNames	Names of groups. If provided, must be a vector of the same length as the list of overlap data frames.
cutoff	Number of retained edges from each overlap data frame after refiltering. If NULL (as default), no refiltering will be performed.
...	Additional parameters passed to <code>henna::radialPlot</code> .

**Details**

The function can separate genes by groups. The groups can be, for instance, different gene sets, or different connected components of the same overlap data frame. A wrapper around `henna::radialPlot`

**Value**

A ggplot object.

**Examples**

```
edgesDF <- data.frame(gene1 = paste0('G', c(1, 2, 3, 4, 7, 8, 10,
11, 11, 10, 10, 10)),
gene2 = paste0('G', c(2, 5, 1, 8, 4, 9, 12,
13, 14, 13, 16, 14)))
edgesDF <- henna::connectedComponents(edgesDF, 'group')
geneRadialPlot(edgesDF, groupLegendTitle='Component', extraCircles=1)
```

---

generateOverlaps

*Generate overlaps of cell sets for input genes*

---

**Description**

This function constructs, for each gene in the expression matrix, a set of cells expressing the gene at or above the input percentile. Subsequently, overlaps of pairs of the constructed cell sets are assessed for statistical significance.

**Usage**

```
generateOverlaps(
  geneSetExp,
  percentile = 90,
  pairs = NULL,
  overlapFileName = NULL
)
```

**Arguments**

<code>geneSetExp</code>	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
<code>percentile</code>	A positive number under 100.
<code>pairs</code>	Pairs of cell sets to be assessed. If NULL (as default), all pairs will be assessed.
<code>overlapFileName</code>	The name of the file where the overlap data frame will be saved. This option can be used to save time when performing exploratory analyses such as trying different <code>jaccardCutoff</code> parameters in <code>breakWeakTies</code> . Default is NULL (the overlap data frame will not be saved).

**Details**

Wrapper around `percentileSets` and `cellSetsOverlaps`.

**Value**

A data frame listing statistics for all cell set overlaps

**Examples**

```
mat <- matrix(0, 2000, 500)
rownames(mat) <- paste0('G', seq(2000))
colnames(mat) <- paste0('C', seq(500))
mat[sample(length(mat), 270000)] <- sample(50, 270000, TRUE)
mat <- mat[paste0('G', sample(2000, 5)), ]
generateOverlaps(mat)
```

---

getPairs

*Get all unordered pairs of two elements from a vector*

---

**Description**

This function returns all unordered pairs of two elements from a vector.

**Usage**

```
getPairs(v)
```

**Arguments**

v                    A vector.

**Value**

A list of vectors of length 2.

**Examples**

```
v <- c('ASD', 'VBN', 'HJKL')
getPairs(v)
```

---

networkPlotDF

*Prepare overlap data frame for network plot*

---

**Description**

This function prepares a ranked and filtered overlap data frame for network plot.

**Usage**

```
networkPlotDF(overlapDF, rankCol = "rank", edgeScale = 2)
```

**Arguments**

overlapDF	Overlap data frame.
rankCol	Name of the rank column.
edgeScale	Scaling factor used in generating edge weights.

**Value**

A data frame ready to serve as input to networkPlot.

---

overlapCutoffPlot      *Plot the selection of overlaps*

---

**Description**

This function illustrates the process of selecting the overlap rank cutoff by plotting rank frequencies against ranks and showcasing the convex hull of the rank-frequency points.

**Usage**

```
overlapCutoffPlot(
  overlapDF,
  title = "Overlap cutoff plot",
  palette = c("purple", "yellow"),
  hullWidth = 0.8,
  xLab = "Overlap rank",
  yLab = "Frequency",
  legendLabs = c("Accepted overlaps", "Discarded overlaps"),
  pointShape = 24,
  ...
)
```

**Arguments**

overlapDF	Processed overlap data frame created with processOverlaps.
title	Plot title.
palette	Color palette. Must have two colors, the first one representing accepted overlaps and the other representing discarded overlaps.
hullWidth	Width of the convex hull.
xLab	x axis label.
yLab	y axis label.
legendLabs	Legend labels.
pointShape	Point shape.
...	Additional arguments passed to henna::hullPlot.

**Details**

A wrapper around henna::hullPlot.

**Value**

A ggplot object.

**Examples**

```
overlapDF <- data.frame(gene1=paste0('G', c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
  gene2=paste0('G', c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
  rank=c(1, 2, 3, 4, 4, 6, 7, 7, 7, 10))
overlapCutoffPlot(overlapDF)
```

---

overlapGenes

*Get all genes from an overlap data frame*

---

**Description**

This function gets all genes from an overlap data frame.

**Usage**

```
overlapGenes(overlapDF, components = NULL)
```

**Arguments**

overlapDF	Overlap data frame.
components	A numeric vector representing the connected components of the overlap data frame graph.

**Value**

A character vector of genes.

**Examples**

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 3)),
  gene1 = paste0('G', c(2, 7, 8)))
overlapGenes(overlapDF)
```

---

overlapNetworkPlot     *Plot the overlaps as a network*

---

### Description

This function plots the graph of the overlap data frame, with genes as vertices and overlaps as edges.

### Usage

```
overlapNetworkPlot(  
  overlapDF,  
  title = "Top overlaps network plot",  
  nodeColor = "orange",  
  edgeColor = "green4",  
  ...  
)
```

### Arguments

overlapDF	Overlap data frame.
title	Plot title.
nodeColor	The color of nodes. If NULL, the default <code>henna::networkPlot</code> color scheme will be used, which uses different colors for nodes belonging to different connected components.
edgeColor	The color of edges.
...	Additional parameters passed to <code>henna::networkPlot</code> .

### Details

A thin wrapper around `henna::networkPlot`.

### Value

An overlap network plot.

### Examples

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 5, 6, 7, 17)),  
  gene2 = paste0('G', c(2, 5, 8, 11, 11, 11)),  
  rank = c(1, 1, 3, 3, 3, 3))  
overlapNetworkPlot(overlapDF)
```

---

overlapPairs	<i>Extract gene pairs from overlap data frame</i>
--------------	---

---

**Description**

This function extracts the gene pairs from an overlap data frame.

**Usage**

```
overlapPairs(overlapDF)
```

**Arguments**

overlapDF      Overlap data frame.

**Value**

A list of gene pairs.

**Examples**

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 3)),
  gene2 = paste0('G', c(2, 7, 8)))
overlapPairs(overlapDF)
```

---

percentileSets	<i>Generates cell expressing input genes at an input percentile</i>
----------------	---

---

**Description**

This function constructs, for each gene in the expression matrix, a set of cells expressing the gene at or above the input percentile.

**Usage**

```
percentileSets(geneSetExp, percentile = 90)
```

**Arguments**

geneSetExp      A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.

percentile      A positive number under 100.

**Value**

A named list of character vectors of length equaling the number of input genes. Each vector stores the cells expressing the gene at or above the input percentile.

**Examples**

```
mat <- matrix(0, 1000, 500)
rownames(mat) <- paste0('G', seq(1000))
colnames(mat) <- paste0('C', seq(500))
mat[sample(length(mat), 70000)] <- sample(50, 70000, TRUE)
mat <- mat[paste0('G', sample(1000, 3)), ]
percentileSets(mat)
```

---

```
prefilterOverlaps      Prefilter overlaps based on adjusted p-value
```

---

**Description**

This function computes adjusted p-value and prefilters overlaps based on it.

**Usage**

```
prefilterOverlaps(overlapDF, mtMethod = c("BY", "BH"))
```

**Arguments**

overlapDF	Overlap data frame.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH'). Default is 'BY'.

**Value**

A prefiltered overlap data frame.

---

```
processOverlaps      Process data frame of overlaps of cell sets
```

---

**Description**

This function filters, ranks and scores previously generated overlaps of cell sets.

**Usage**

```
processOverlaps(
  overlapDF,
  mtMethod = c("BY", "BH"),
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  ...
)
```

**Arguments**

overlapDF	Overlap data frame.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH'). Default is 'BY'.
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".
...	Additional arguments passed to mtCorrectDF.

**Details**

Wrapper around byCorrectDF, rankOverlaps, prepareFiltering, filterOverlaps and scoreOverlaps. If jaccardCutoff is not NULL, it also calls breakWeakTies between filterOverlaps and scoreOverlaps.

**Value**

A data frame consisting of filtered, ranked and scored cell sets overlaps

**Examples**

```
overlapDF <- data.frame(gene1=paste0('G',
c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
gene2=paste0('G',
c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
ratio=runif(10, 2, 10),
pval=runif(10, 0, 1e-10))
processOverlaps(overlapDF)
```

---

qGrab

*Read and delete a .qs2 file*


---

**Description**

This functions reads a .qs2 file, deletes it, and returns its content.

**Usage**

```
qGrab(qs2File)
```

**Arguments**

qs2File	Name of .qs2 file with path.
---------	------------------------------

**Value**

The content of the .qs2 file.

**Examples**

```
library(qs2)
qs_save(c(1, 2, 3), 'temp.qs2')
qGrab('temp.qs2')
```

runCSOA

*Run the CSOA pipeline***Description**

This function generates cell set overlaps for input gene sets based on percentiles of gene expression, computes the significance of these overlaps, ranks, filters and scores the overlaps, and builds a per-cell score by summing the products of overlap scores and the min-max-normalized expression of the corresponding pairs of genes.

**Usage**

```
runCSOA(
  scObj,
  geneSets,
  percentile = 90,
  mtMethod = c("BY", "BH"),
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  overlapFileName = NULL,
  pairFileTemplate = NULL,
  keepOverlapOrder = FALSE,
  ...
)
```

**Arguments**

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
geneSets	Named list of character vectors of which each must contain at least two genes.
percentile	A positive number under 100.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH'). Default is 'BY'.
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".
overlapFileName	The name of the file where the overlap data frame will be saved. This option can be used to save time when performing exploratory analyses such as trying different jaccardCutoff parameters in breakWeakTies. Default is NULL (the overlap data frame will not be saved).
pairFileTemplate	Character object used in the naming of the files where the pair data frames will be saved. Default is NULL (the pair data frames will not be saved).

```

keepOverlapOrder
    Keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. Ignored if pairFileTemplate is NULL.
...
    Additional arguments.

```

## Details

Wrapper around `expMat`, `generateOverlaps`, `scoreCells` and `attachCellScores`.

## Value

An object of the same class as `scObj` with per-gene-set CSOA scores assigned for each cell.

## Examples

```

mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes <- paste0('G', seq(200))
mat[genes, 20:50] <- matrix(runif(200 * 31, min = 14, max = 15),
  nrow = 200, ncol = 31)
geneSet1 <- paste0('G', seq(1, 150))
geneSet2 <- paste0('G', seq(50, 200))
df <- runCSOA(mat, list(a = geneSet1, b = geneSet2))
head(df)

```

---

scoreCells

*Generate CSOA scores from overlap data frame and list of pairs*

---

## Description

This function scores an overlap data frame using its associated list of pairs. The overlap data frame is split based on the overlaps corresponding to each gene set and scored, and the output is rejoined as a data frame.

## Usage

```

scoreCells(
  geneSetExp,
  overlapDF,
  setPairs,
  geneSetNames,
  mtMethod = c("BY", "BH"),
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileTemplate = NULL,
  keepOverlapOrder = FALSE,
  ...
)

```

**Arguments**

geneSetExp	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
overlapDF	Overlap data frame.
setPairs	A list of overlaps corresponding to each input gene set.
geneSetNames	Character vector of names of gene sets.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg ('BH'). Default is 'BY'.
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".
pairFileTemplate	Character object used in the naming of the files where the pair data frames will be saved. Default is NULL (the pair data frames will not be saved).
keepOverlapOrder	Keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. Ignored if pairFileTemplate is NULL.
...	Additional arguments passed to mtCorrectDF.

**Details**

This function calls scoreCells to score each gene set data frame split from the full overlap data frame.

**Value**

A data frame whose columns correspond to the CSOA scores of the input gene sets.

**Examples**

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes <- paste0('G', seq(200))
mat[genes, 20:50] <- matrix(runif(200 * 31, min=14, max=15),
  nrow=200, ncol=31)
geneSet1 <- paste0('G', seq(1, 150))
geneSet2 <- paste0('G', seq(50, 200))
geneSets <- list(geneSet1, geneSet2)
geneSets <- lapply(geneSets, sort)
setPairs <- lapply(geneSets, getPairs)
pairs <- Reduce(union, setPairs)
genes <- union(geneSet1, geneSet2)
mat <- mat[genes, ]
overlapDF <- generateOverlaps(mat, pairs=pairs)
scoreDF <- scoreCells(mat, overlapDF, setPairs, c('set1', 'set2'))
head(scoreDF)
```

---

scoreCellsCore	<i>Generate CSOA scores from overlap data frame for a single gene set</i>
----------------	---

---

### Description

This function computes per-cell CSOA scores from overlap data frame for a single gene set.

### Usage

```
scoreCellsCore(
  geneSetExp,
  overlapDF,
  colStr = "CSOA",
  mtMethod = c("BY", "BH"),
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileName = NULL,
  keepOverlapOrder = FALSE,
  ...
)
```

### Arguments

geneSetExp	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
overlapDF	Overlap data frame.
colStr	Name of column where CSOA scores will be stored.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg ('BH'). Default is 'BY'.
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".
pairFileName	The name of the file where the pair data frame will be saved.
keepOverlapOrder	Whether to keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order.
...	Additional arguments passed to mtCorrectDF.

### Value

A data frame with a column corresponding to the CSOA scores.

---

scoreModules	<i>Run CSOA separately on the connected components of the overlap graph</i>
--------------	---

---

### Description

This function runs CSOA on the connected components of the graph having the filtered overlaps as edges.

### Usage

```
scoreModules(
  scObj,
  networkDF,
  components,
  colStrTemplate = "CSOA_component",
  ...
)
```

### Arguments

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
networkDF	A data frame with gene1, gene2 and component columns.
components	A numeric vector representing the connected components of the overlap data frame graph.
colStrTemplate	Character used in the naming of the component gene sets.
...	Additional parameters passed to runCSOAMultiple.

### Value

An object of the same class as scObj with CSOA scores corresponding to the genes defining each connected components assigned for each cell.

### Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes1 <- paste0('G', seq(100))
mat[genes1, 20:50] <- matrix(runif(100 * 31, min = 14, max = 15),
  nrow = 100, ncol = 31)
genes2 <- paste0('G', seq(101, 200))
mat[genes2, 70:100] <- matrix(runif(100 * 31, min = 14, max = 15),
  nrow = 100, ncol = 31)
genes <- union(genes1, genes2)
mat <- mat[genes, ]
overlapDF <- generateOverlaps(mat)
overlapDF <- processOverlaps(overlapDF)
overlapDF <- henna::connectedComponents(overlapDF)
df <- scoreModules(mat, overlapDF, unique(overlapDF$component))[[2]]
head(df)
```

# Index

## \* internal

- computePairScores, [7](#)
- computePCPairScores, [8](#)
- CSOA-package, [2](#)
- edgeLists.default, [8](#)
- networkPlotDF, [13](#)
- prefilterOverlaps, [18](#)
- scoreCellsCore, [23](#)

- attachCellScores
  - (attachCellScores.default), [3](#)
- attachCellScores.default, [3](#)

- basicHeatmap, [4](#)
- breakWeakTies, [5](#)

- cellDistribution, [6](#)
- cellSetsOverlaps, [6](#)
- computePairScores, [7](#)
- computePCPairScores, [8](#)
- CSOA (CSOA-package), [2](#)
- CSOA-package, [2](#)

- edgeLists (edgeLists.default), [8](#)
- edgeLists.default, [8](#)
- expMat, [9](#)

- featureWes, [10](#)

- geneRadialPlot, [11](#)
- generateOverlaps, [12](#)
- getPairs, [13](#)

- networkPlotDF, [13](#)

- overlapCutoffPlot, [14](#)
- overlapGenes, [15](#)
- overlapNetworkPlot, [16](#)
- overlapPairs, [17](#)

- percentileSets, [17](#)
- prefilterOverlaps, [18](#)
- processOverlaps, [18](#)

- qGrab, [19](#)

- runCSOA, [20](#)

- scoreCells, [21](#)
- scoreCellsCore, [23](#)
- scoreModules, [24](#)