

Package ‘alabaster.ranges’

May 1, 2026

Title Load and Save Ranges-related Artifacts from File

Version 1.13.0

Date 2025-07-22

License MIT + file LICENSE

Description Save GenomicRanges, IRanges and related data structures into file artifacts, and load them back into memory.

This is a more portable alternative to serialization of such objects into RDS files.

Each artifact is associated with metadata for further interpretation;

downstream applications can enrich this metadata with context-specific properties.

Depends GenomicRanges, alabaster.base

Imports methods, S4Vectors, BiocGenerics, IRanges, Seqinfo, rhdf5

Suggests testthat, knitr, BiocStyle, jsonlite

VignetteBuilder knitr

RoxygenNote 7.2.3

biocViews DataImport, DataRepresentation

git_url <https://git.bioconductor.org/packages/alabaster.ranges>

git_branch devel

git_last_commit 907364c

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-05-01

Author Aaron Lun [aut, cre]

Maintainer Aaron Lun <infinite.monkeys.with.keyboards@gmail.com>

Contents

| | |
|--|----|
| readAtomicVectorList | 2 |
| readDataFrameList | 3 |
| readGRanges | 4 |
| readGRangesList | 5 |
| readSeqinfo | 5 |
| saveObject,CompressedAtomicList-method | 6 |
| saveObject,CompressedSplitDataFrameList-method | 7 |
| saveObject,GRanges-method | 8 |
| saveObject,GRangesList-method | 9 |
| saveObject,Seqinfo-method | 10 |

readAtomicVectorList *Load an atomic vector list*

Description

Load a list of atomic vectors as a [CompressedAtomicList](#) from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in [readObject](#).

Usage

```
readAtomicVectorList(path, metadata, ...)
```

Arguments

| | |
|----------|--|
| path | String containing a path to a directory, itself created with the saveObject method for CompressedAtomicLists . |
| metadata | Named list of metadata for this object, see readObjectFile for details. |
| ... | Further arguments, to be passed to internal altReadObject calls. |

Value

A [CompressedAtomicList](#) of the relevant type.

Author(s)

Aaron Lun

See Also

"[saveObject, CompressedAtomicList-method](#)", to save an object to disk.

Examples

```
library(S4Vectors)
X <- splitAsList(LETTERS, sample(3, 26, replace=TRUE))

tmp <- tempfile()
saveObject(X, tmp)
readObject(tmp)
```

| | |
|-------------------|-------------------------------|
| readDataFrameList | <i>Load a data frame list</i> |
|-------------------|-------------------------------|

Description

Load a list of data frames as a [CompressedSplitDataFrameList](#) from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in [readObject](#).

Usage

```
readDataFrameList(path, metadata, ...)
```

Arguments

| | |
|----------|--|
| path | String containing a path to a directory, itself created with the saveObject method for CompressedSplitDataFrameList objects. |
| metadata | Named list of metadata for this object, see readObjectFile for details. |
| ... | Further arguments, to be passed to internal altReadObject calls. |

Value

A [CompressedSplitDataFrameList](#).

Author(s)

Aaron Lun

See Also

["saveObject, CompressedSplitDataFrameList-method"](#), to save an object to disk.

Examples

```
library(S4Vectors)
Y <- splitAsList(DataFrame(Xxx=LETTERS, Yyy=1:26), sample(3, 26, replace=TRUE))

tmp <- tempfile()
saveObject(Y, tmp)
readObject(tmp)
```

| | |
|-------------|---------------------------------|
| readGRanges | <i>Read a GRanges from disk</i> |
|-------------|---------------------------------|

Description

Read a [GRanges](#) object from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in [readObject](#).

Usage

```
readGRanges(path, metadata, ...)
```

Arguments

| | |
|----------|---|
| path | String containing a path to a directory, itself created with the stageObject method for GRanges . |
| metadata | Named list of metadata for this object, see readObjectFile for details. |
| ... | Further arguments to pass to internal altReadObject calls. |

Value

A [GRanges](#) object.

Author(s)

Aaron Lun

See Also

"[saveObject, GRanges-method](#)", to save a [GRanges](#) to disk.

Examples

```
gr <- GRanges(c("chrA", "chrB"), IRanges(c(1, 5), c(100, 200)))
seqlengths(gr) <- c(chrA=1000, chrB=2000)

tmp <- tempfile()
saveObject(gr, tmp)
readObject(tmp)
```

| | |
|-----------------|-------------------------------------|
| readGRangesList | <i>Read a GRangesList from disk</i> |
|-----------------|-------------------------------------|

Description

Read a [GRangesList](#) object from its on-disk representation.

Usage

```
readGRangesList(path, metadata, ...)
```

Arguments

| | |
|----------|---|
| path | String containing a path to a directory, itself created with the saveObject method for GRangesLists . |
| metadata | Named list of metadata for this object, see readObjectFile for details. |
| ... | Further arguments, to be passed to internal altReadObject calls. |

Value

A [GRangesList](#) object.

Examples

```
gr <- GRanges(c("chrA", "chrB"), IRanges(c(1, 5), c(100, 200)))
seqlengths(gr) <- c(chrA=1000, chrB=2000)
gr1 <- split(gr, rep(1:3, length.out=length(gr)))

tmp <- tempfile()
saveObject(gr1, tmp)
readObject(tmp)
```

| | |
|-------------|---------------------------------|
| readSeqinfo | <i>Read a Seqinfo from disk</i> |
|-------------|---------------------------------|

Description

Read a [Seqinfo](#) object from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in [readObject](#).

Usage

```
readSeqinfo(path, metadata, ...)
```

Arguments

| | |
|----------|---|
| path | String containing a path to a directory, itself created with the saveObject method for Seqinfo objects. |
| metadata | Named list of metadata for this object, see readObjectFile for details. |
| ... | Further arguments, ignored. |

Value

A [Seqinfo](#) object.

See Also

"[saveObject,Seqinfo-method](#)" for the corresponding saving method.

Examples

```
si <- Seqinfo(c("chrA", "chrB"), c(1000, 2000))

tmp <- tempfile()
saveObject(si, tmp)
readObject(tmp)
```

saveObject,CompressedAtomicList-method

Save compressed list of atomic vectors to disk

Description

Save a [CompressedAtomicList](#) object to its on-disk representation.

Usage

```
## S4 method for signature 'CompressedAtomicList'
saveObject(x, path, ...)
```

Arguments

| | |
|------|---|
| x | A CompressedAtomicList object. |
| path | String containing the path to a directory in which to save x. |
| ... | Further arguments to pass to specific methods. |

Value

x is saved to path, and NULL is invisibly returned.

Author(s)

Aaron Lun

See Also

[readAtomicVectorList](#), to read a [CompressedAtomicList](#) from disk.

Examples

```
library(S4Vectors)
X <- splitAsList(LETTERS, sample(3, 26, replace=TRUE))

tmp <- tempfile()
saveObject(X, tmp)
list.files(tmp, recursive=TRUE)
```

saveObject,CompressedSplitDataFrameList-method

Save compressed lists of data frames to disk

Description

Save a [CompressedSplitDataFrameList](#) object to its on-disk representation.

Usage

```
## S4 method for signature 'CompressedSplitDataFrameList'
saveObject(x, path, ...)
```

Arguments

| | |
|------|---|
| x | A CompressedSplitDataFrameList object. |
| path | String containing the path to a directory in which to save x. |
| ... | Further arguments to pass to specific methods. |

Value

x is saved to path, and NULL is invisibly returned.

Author(s)

Aaron Lun

See Also

[readDataFramelist](#), to read a [CompressedSplitDataFrameList](#) from disk.

Examples

```
library(S4Vectors)
Y <- splitAsList(DataFrame(Xxx=LETTERS, Yyy=1:26), sample(3, 26, replace=TRUE))

tmp <- tempfile()
saveObject(Y, tmp)
list.files(tmp, recursive=TRUE)
```

saveObject,GRanges-method

Save a GRanges object to disk

Description

Save a [GRanges](#) object to its on-disk representation .

Usage

```
## S4 method for signature 'GRanges'  
saveObject(x, path, ...)
```

Arguments

| | |
|------|---|
| x | A GRanges object or one of its subclasses. |
| path | String containing the path to a directory in which to save x. |
| ... | Further arguments to pass to specific methods. |

Value

x is saved to path, and NULL is invisibly returned.

Author(s)

Aaron Lun

See Also

[readGRanges](#), to read a [GRanges](#) from disk.

Examples

```
gr <- GRanges(c("chrA", "chrB"), IRanges(c(1, 5), c(100, 200)))  
seqlengths(gr) <- c(chrA=1000, chrB=2000)  
  
tmp <- tempfile()  
saveObject(gr, tmp)  
list.files(tmp, recursive=TRUE)
```

`saveObject,GRangesList-method`*Save a GRangesList object to disk*

Description

Save a [GRangesList](#) object to its on-disk representation.

Usage

```
## S4 method for signature 'GRangesList'  
saveObject(x, path, ...)
```

Arguments

| | |
|-------------------|---|
| <code>x</code> | A GRangesList object. |
| <code>path</code> | String containing the path to a directory in which to save <code>x</code> . |
| <code>...</code> | Further arguments to pass to specific methods. |

Value

`x` is saved to `path`, and `NULL` is invisibly returned.

Author(s)

Aaron Lun

See Also

[readGRangesList](#), to read a [GRangesList](#) from disk.

Examples

```
gr <- GRanges("chrA", IRanges(1:100, width=1))  
grl <- split(gr, rep(1:3, length.out=length(gr)))  
  
tmp <- tempfile()  
saveObject(grl, tmp)  
list.files(tmp, recursive=TRUE)
```

saveObject,Seqinfo-method

Save a Seqinfo object to disk

Description

Save a [Seqinfo](#) object to its on-disk representation.

Usage

```
## S4 method for signature 'Seqinfo'  
saveObject(x, path, ...)
```

Arguments

| | |
|------|---|
| x | A Seqinfo object. |
| path | String containing the path to a directory in which to save x. |
| ... | Further arguments to pass to specific methods. |

Value

x is saved to path, and NULL is invisibly returned.

See Also

[readSeqinfo](#), to read a [Seqinfo](#) from disk.

Examples

```
si <- Seqinfo(c("chrA", "chrB"), c(1000, 2000))  
  
tmp <- tempfile()  
dir.create(tmp)  
saveObject(si, tmp, path="seqinfo")  
list.files(tmp, recursive=TRUE)
```

Index

altReadObject, 2–5

CompressedAtomicList, 2, 6

CompressedSplitDataFrameList, 3, 7

GRanges, 4, 8

GRangesList, 5, 9

loadAtomicVectorList
 (readAtomicVectorList), 2

loadDataFrameList (readDataFrameList), 3

loadGRanges (readGRanges), 4

loadGRangesList (readGRangesList), 5

loadSeqinfo (readSeqinfo), 5

readAtomicVectorList, 2, 6

readDataFrameList, 3, 7

readGRanges, 4, 8

readGRangesList, 5, 9

readObject, 2–5

readObjectFile, 2–5

readSeqinfo, 5, 10

saveObject, 2, 3, 5

saveObject, CompressedAtomicList-method,
 6

saveObject, CompressedSplitDataFrameList-method,
 7

saveObject, GRanges-method, 8

saveObject, GRangesList-method, 9

saveObject, Seqinfo-method, 10

Seqinfo, 5, 6, 10

stageObject, 4

stageObject, CompressedAtomicList-method
 (saveObject, CompressedAtomicList-method),
 6

stageObject, CompressedSplitDataFrameList-method
 (saveObject, CompressedSplitDataFrameList-method),
 7

stageObject, GRanges-method
 (saveObject, GRanges-method), 8

stageObject, GRangesList-method
 (saveObject, GRangesList-method),
 9

stageObject, Seqinfo-method
 (saveObject, Seqinfo-method), 10