

# Package ‘dominatRData’

April 30, 2026

**Type** Package

**Title** Datasets for R Package dominatR

**Version** 1.1.0

**Description** dominatRData is a data package useful for showcasing dominatR examples. dominatR is an R package for quantifying and visualizing feature dominance in datasets. dominatR makes use of entropy-based triangular projections and compositional comparison metrics.

**License** MIT + file LICENSE

**Encoding** UTF-8

**biocViews** ExperimentData, ChIPSeqData, Tissue, PackageTypeData

**LazyData** false

**URL** <https://github.com/VanBortleLab/dominatRData>

**BugReports** <https://github.com/VanBortleLab/dominatRData/issues>

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Depends** R (>= 4.5.0)

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/dominatRData>

**git\_branch** devel

**git\_last\_commit** f277c56

**git\_last\_commit\_date** 2026-04-28

**Repository** Bioconductor 3.24

**Date/Publication** 2026-04-30

**Author** Simon Lizarazo [aut, cre] (ORCID:  
<<https://orcid.org/0009-0001-8974-6225>>),  
Ethan Chen [ctb],  
Rajendra K C [ctb],  
Kevin Van Bortle [ctb]

**Maintainer** Simon Lizarazo <[silizarazoch@gmail.com](mailto:silizarazoch@gmail.com)>

## Contents

atac_tissue_counts . . . . .	2
atac_tissue_score . . . . .	3
rnapol_counts . . . . .	3
rnapol_score . . . . .	4
<b>Index</b>	<b>5</b>

---

atac_tissue_counts	<i>ATAC-Seq rawcounts for POL3 Genes Dataframe</i>
--------------------	--

---

## Description

A list of tissues and the corresponding counts for RNA POL3 genes for each of them.

## Usage

```
data('atac_tissue_counts')
```

## Format

A dataframe with 9817 rows and 26 variables:

**core\_type** Category for genes based on their expression across tissues

**Chr** Chromosome where the RNA of interest is located

**Start** Gene start coordinate

**End** Gene end coordinate

**Gene** Gene name

**Index** Unique RNA Sequence identifier - Can be retrieved from RNA Central

**Type** Type of RNA POL3 Transcript

**Tissue** Remaining columns contain the name of different assessed tissues

## Source

Created by The VanBortle lab at UIUC to serve as an example

## References

Simon Lizarazo et al., 2025 bioRxiv Preprint

---

atac\_tissue\_score      *ATAC-Seq Score for POL3 Genes Dataframe*

---

### Description

A list of tissues and the corresponding counts for RNA POL3 genes for each of them. Values represent a binary call on significance for accessibility. If the value is 1 the gene is accessible in the respective tissue.

### Usage

```
data('atac_tissue_score')
```

### Format

A dataframe with 9817 rows and 23 variables:

**core\_type** Category for genes based on their expression across tissues

**Chr** Chromosome where the RNA of interest is located

**Start** Gene start coordinate

**End** Gene end coordinate

**Gene** Gene name

**Index** Unique RNA Sequence identifier - Can be retrieved from RNA Central

**Type** Type of RNA POL3 Transcript

**Tissue** Remaining columns contain the name of different assessed tissues

### Source

Created by The VanBortle lab at UIUC to serve as an example

### References

Simon Lizarazo et al., 2025 bioRxiv Preprint

---

rnapol\_counts      *RNA Polymerase raw counts dataframe*

---

### Description

A subset of data obtained from CHIP-Seq Data for RNA Polymerase I, II and III

### Usage

```
data('rnapol_counts')
```

**Format**

A dataframe with 1061 rows and 7 variables:

**Chr** Chromosome where the gene is located

**Start** Gene start coordinate

**Stop** Gene stop coordinate

**RNA\_Type** Type of transcript

**pol1** Raw counts for RNA Polymerase I Chip-Seq

**pol2** Raw counts for RNA Polymerase II Chip-Seq

**pol3** Raw counts for RNA Polymerase III Chip-Seq

**Source**

Created by The VanBortle lab at UIUC to serve as an example

**References**

Rajendra K C et al., 2024 Molecular Cell

---

rnapol\_score

*RNA Polymerase score dataframe*

---

**Description**

A subset of data obtained from CHIP-Seq Data for RNA Polymerase I, II and III. Values are represented as the  $-\log_{10}(\text{p-value})$

**Usage**

```
data('rnapol_score')
```

**Format**

A dataframe with 1061 rows and 7 variables:

**Chr** Chromosome where the gene is located

**Start** Gene start coordinate

**Stop** Gene stop coordinate

**RNA\_Type** Type of transcript

**pol1** Score for RNA Polymerase I Chip-Seq

**pol2** Score for RNA Polymerase II Chip-Seq

**pol3** Score for RNA Polymerase III Chip-Seq

**Source**

Created by The VanBortle lab at UIUC to serve as an example

**References**

Rajendra K C et al., 2024 Molecular Cell

# Index

atac\_tissue\_counts, 2

atac\_tissue\_score, 3

rnapol\_counts, 3

rnapol\_score, 4