

# Package ‘Nebulosa’

April 24, 2025

**Type** Package

**Title** Single-Cell Data Visualisation Using Kernel Gene-Weighted  
Density Estimation

**Version** 1.18.0

**Description** This package provides an enhanced visualization of single-cell data based on gene-weighted density estimation. Nebulosa recovers the signal from dropped-out features and allows the inspection of the joint expression from multiple features (e.g. genes). Seurat and SingleCellExperiment objects can be used within Nebulosa.

**URL** <https://github.com/powellgenomicslab/Nebulosa>

**BugReports** <https://github.com/powellgenomicslab/Nebulosa/issues>

**License** GPL-3

**Encoding** UTF-8

**Depends** R (>= 4.0), ggplot2, patchwork

**Imports** SingleCellExperiment, SummarizedExperiment, SeuratObject, ks,  
Matrix, stats, methods, ggrastr

**RoxygenNote** 7.2.3

**VignetteBuilder** knitr

**Suggests** testthat, BiocStyle, knitr, rmarkdown, covr, scater, scan,  
DropletUtils, igraph, BiocFileCache, Seurat

**biocViews** Software, GeneExpression, SingleCell, Visualization,  
DimensionReduction

**git\_url** <https://git.bioconductor.org/packages/Nebulosa>

**git\_branch** RELEASE\_3\_21

**git\_last\_commit** f80b748

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.21

**Date/Publication** 2025-04-23

**Author** Jose Alquicira-Hernandez [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-9049-7780>>)

**Maintainer** Jose Alquicira-Hernandez <alquicirajose@gmail.com>

Contents

|                             |          |
|-----------------------------|----------|
| calculate_density . . . . . | 2        |
| plot_density . . . . .      | 3        |
| plot_density_ . . . . .     | 5        |
| wkde2d . . . . .            | 6        |
| <b>Index</b>                | <b>8</b> |

---

|                   |                                         |
|-------------------|-----------------------------------------|
| calculate_density | <i>Estimate weighted kernel density</i> |
|-------------------|-----------------------------------------|

---

Description

Estimate weighted kernel density

Usage

```
calculate_density(w, x, method, adjust = 1, map = TRUE)
```

Arguments

|        |                                                                                                                                                                                                                                                                                                                                       |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| w      | Vector with weights for each observation                                                                                                                                                                                                                                                                                              |
| x      | Matrix with dimensions where to calculate the density from. Only the first two dimensions will be used                                                                                                                                                                                                                                |
| method | Kernel density estimation method: <ul style="list-style-type: none"><li>• ks: Computes density using the kde function from the ks package.</li><li>• wkde: Computes density using a modified version of the kde2d function from the MASS package to allow weights. Bandwidth selection from the ks package is used instead.</li></ul> |
| adjust | Numeric value to adjust to bandwidth. Default: 1. Not available for ks method                                                                                                                                                                                                                                                         |
| map    | Whether to map densities to individual observations                                                                                                                                                                                                                                                                                   |

Value

If map is TRUE, a vector with corresponding densities for each observation is returned. Otherwise, a list with the density estimates from the selected method is returned.

Author(s)

Jose Alquicira-Hernandez

Examples

```
dens <- Nebulosa:::calculate_density(iris[, 3], iris[, 1:2], method = "wkde")
```

---

|              |                                             |
|--------------|---------------------------------------------|
| plot_density | <i>Plot gene-weighted 2D kernel density</i> |
|--------------|---------------------------------------------|

---

**Description**

Plot gene-weighted 2D kernel density

**Usage**

```
plot_density(  
  object,  
  features,  
  slot = NULL,  
  joint = FALSE,  
  reduction = NULL,  
  dims = c(1, 2),  
  method = c("ks", "wkde"),  
  adjust = 1,  
  size = 1,  
  shape = 16,  
  combine = TRUE,  
  pal = "viridis",  
  raster = TRUE,  
  ...  
)
```

```
## S4 method for signature 'Seurat'
```

```
plot_density(  
  object,  
  features,  
  slot = NULL,  
  joint = FALSE,  
  reduction = NULL,  
  dims = c(1, 2),  
  method = c("ks", "wkde"),  
  adjust = 1,  
  size = 1,  
  shape = 16,  
  combine = TRUE,  
  pal = "viridis",  
  raster = TRUE,  
  ...  
)
```

```
## S4 method for signature 'SingleCellExperiment'
```

```
plot_density(  
  object,
```

```

features,
slot = NULL,
joint = FALSE,
reduction = NULL,
dims = c(1, 2),
method = c("ks", "wkde"),
adjust = 1,
size = 1,
shape = 16,
combine = TRUE,
pal = "viridis",
raster = TRUE,
...
)

```

### Arguments

|           |                                                                                                                                                                                                                                                                                                                                          |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object    | Seurat or SingleCellExperiment object                                                                                                                                                                                                                                                                                                    |
| features  | Features (e.g. genes) to visualize                                                                                                                                                                                                                                                                                                       |
| slot      | Type of data: counts or data for Seurat objects and counts, logcounts, or normcounts for SingleCellExperiment objects                                                                                                                                                                                                                    |
| joint     | Return joint density plot? By default FALSE                                                                                                                                                                                                                                                                                              |
| reduction | Name of the reduction to visualize. If not provided, last computed reduction is visualized                                                                                                                                                                                                                                               |
| dims      | Vector of length 2 specifying the dimensions to be plotted. By default, the first two dimensions are considered.                                                                                                                                                                                                                         |
| method    | Kernel density estimation method: <ul style="list-style-type: none"> <li>• ks: Computes density using the kde function from the ks package.</li> <li>• wkde: Computes density using a modified version of the kde2d function from the MASS package to allow weights. Bandwidth selection from the ks package is used instead.</li> </ul> |
| adjust    | Numeric value to adjust to bandwidth. Default: 1. Not available for ks method                                                                                                                                                                                                                                                            |
| size      | Size of the geom to be plotted (e.g. point size)                                                                                                                                                                                                                                                                                         |
| shape     | Shape of the geom to be plotted                                                                                                                                                                                                                                                                                                          |
| combine   | Create a single plot? If FALSE, a list with ggplot objects is returned                                                                                                                                                                                                                                                                   |
| pal       | String specifying the viridis color palette to use.                                                                                                                                                                                                                                                                                      |
| raster    | Rasterise plot                                                                                                                                                                                                                                                                                                                           |
| ...       | Further scale arguments passed to scale_color_viridis_c Options: <ul style="list-style-type: none"> <li>• viridis</li> <li>• magma</li> <li>• cividis</li> <li>• inferno</li> <li>• plasma</li> </ul>                                                                                                                                    |

**Value**

A scatterplot from a given reduction showing the gene-weighted density

**Methods (by class)**

- plot\_density(Seurat): Plot gene-weighted 2D kernel density
- plot\_density(SingleCellExperiment): Plot gene-weighted 2D kernel density

**Author(s)**

Jose Alquicira-Hernandez

**Examples**

```
data <- SeuratObject::pbmc_small
plot_density(data, "CD3E")
```

---

|               |                               |
|---------------|-------------------------------|
| plot_density_ | <i>Plot density estimates</i> |
|---------------|-------------------------------|

---

**Description**

Plot density estimates

**Usage**

```
plot_density_(
  z,
  feature,
  cell_embeddings,
  dim_names,
  shape,
  size,
  legend_title,
  pal = c("viridis", "magma", "cividis", "inferno", "plasma"),
  raster,
  ...
)
```

**Arguments**

|                 |                                                  |
|-----------------|--------------------------------------------------|
| z               | Vector with density values for each cells        |
| feature         | Name of the feature being plotted                |
| cell_embeddings | Matrix with cell embeddings                      |
| dim_names       | Names of the dimensions from the cell embeddings |

|              |                                                         |
|--------------|---------------------------------------------------------|
| shape        | Geom shape                                              |
| size         | Geom size                                               |
| legend_title | String used as legend title                             |
| pal          | String specifying the viridis color palette to use      |
| raster       | Rasterise plot                                          |
| ...          | Further scale arguments passed to scale_color_viridis_c |

**Value**

A ggplot object

**Author(s)**

Jose Alquicira-Hernandez

---

|        |                                              |
|--------|----------------------------------------------|
| wkde2d | <i>Weighted 2D kernel density estimation</i> |
|--------|----------------------------------------------|

---

**Description**

Weighted 2D kernel density estimation

**Usage**

wkde2d(x, y, w, h, adjust = 1, n = 100, lims = c(range(x), range(y)))

**Arguments**

|        |                                                                                                                                                          |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| x      | Dimension 1                                                                                                                                              |
| y      | Dimension 2                                                                                                                                              |
| w      | Weight variable                                                                                                                                          |
| h      | vector of bandwidths for x and y directions. Defaults to normal reference bandwidth (ks::hpi). A scalar value will be taken to apply to both directions. |
| adjust | Bandwidth adjustment                                                                                                                                     |
| n      | Number of grid points in each direction. Can be scalar or a length-2 integer vector.                                                                     |
| lims   | The limits of the rectangle covered by the grid as c(xl, xu, yl, yu).                                                                                    |

**Value**

A list of three components.

- x, y The x and y coordinates of the grid points, vectors of length n.
- z An n[1] by n[2] matrix of the weighted estimated density: rows correspond to the value of x, columns to the value of y.

**Author(s)**

Jose Alquicira-Hernandez

**Examples**

```
set.seed(1)
x <- rnorm(100)

set.seed(2)
y <- rnorm(100)

set.seed(3)
w <- sample(c(0, 1), 100, replace = TRUE)

dens <- Nebulosa::wkde2d(x, y, w)
```

# Index

`calculate_density`, [2](#)

`plot_density`, [3](#)

`plot_density`, Seurat-method

    (`plot_density`), [3](#)

`plot_density`, SingleCellExperiment-method

    (`plot_density`), [3](#)

`plot_density_`, [5](#)

`wkde2d`, [6](#)