Package 'scRepertoire'

April 22, 2025

Title A toolkit for single-cell immune receptor profiling

Version 2.4.0

Description
scRepertoire is a toolkit for processing and analyzing single-cell T-cell receptor (TCR) and immunoglobulin (Ig). The scRepertoire framework supports use of 10x, AIRR, BD, MiXCR, Omniscope, TRUST4, and WAT3R single-cell formats. The functionality includes basic clonal analyses, repertoire summaries, distance-based clustering and interaction with the popular Seurat and SingleCellExperiment/Bioconductor R workflows.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

biocViews Software, ImmunoOncology, SingleCell, Classification, Annotation, Sequencing

Depends ggplot2, R (>= 4.0)

Imports assertthat, cubature, dplyr, evmix, ggalluvial, ggdendro, ggraph, grDevices, igraph, iNEXT, plyr, quantreg, Rcpp, reshape2, rjson, rlang, S4Vectors, SeuratObject, SingleCellExperiment, stringr, stringdist, SummarizedExperiment, tidygraph, truncdist, VGAM, purrr, lifecycle, methods

Suggests BiocManager, BiocStyle, circlize, knitr, rmarkdown, scales, scater, Seurat, spelling, testthat (>= 3.0.0), vdiffr, withr

VignetteBuilder knitr

Config/testthat/edition 3

Language en-US

LinkingTo Rcpp

URL https://www.borch.dev/uploads/scRepertoire/

BugReports https://github.com/BorchLab/scRepertoire/issues

Roxygen list(markdown = TRUE)

git_url https://git.bioconductor.org/packages/scRepertoire

git_branch RELEASE_3_21

git_last_commit 211fa9d

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-04-21

Author Nick Borcherding [aut, cre],
Qile Yang [aut],
Ksenia Safina [aut]

Maintainer Nick Borcherding <ncborch@gmail.com>

Contents

scRepertoire-package . . . 3
addVariable . . . 4
alluvialClones . . . 4
clonalAbundance . . . 6
clonalBias . . . 7
clonalCluster . . . 8
clonalCompare . . . 9
clonalDiversity . . . 11
clonalHomeostasis . . . 13
clonalLength . . . 14
clonalNetwork . . . 15
clonalOccupy . . . 17
clonalOverlap . . . 18
clonalOverlay . . . 20
clonalProportion . . . 21
clonalQuant . . . 22
clonalRarefaction . . . 23
clonalScatter . . . 24
clonalSizeDistribution . . . 26
combineBCR . . . 27
combineExpression . . . 29
combineTCR . . . 30
contig_list . . . 31
createHTOContigList . . . 31
exportClones . . . 32
expression2List . . . 33
getCirclize . . . 34
getContigDoublets . . . 35
getHumanIgPseudoGenes . . . 36
highlightClones . . . 36
loadContigs . . . 37
mini_contig_list . . . 38

percentAA 39
percentGenes 40
percentKmer 41
percentVJ 42
positionalEntropy 43
positionalProperty 44
quietVDJgenes 45
scRep_example 46
StartracDiversity 46
subsetClones 48
vizGenes 48

Index **50**

`scRepertoire-package` *scRepertoire: A toolkit for single-cell immune receptor profiling*

Description

scRepertoire is a toolkit for processing and analyzing single-cell T-cell receptor (TCR) and immunoglobulin (Ig). The scRepertoire framework supports use of 10x, AIRR, BD, MiXCR, Omniscope, TRUST4, and WAT3R single-cell formats. The functionality includes basic clonal analyses, repertoire summaries, distance-based clustering and interaction with the popular Seurat and SingleCellExperiment/Bioconductor R workflows.

Author(s)

Maintainer: Nick Borcherding <ncborch@gmail.com>

Authors:

- Qile Yang <qile.yang@berkeley.edu>
- Ksenia Safina <safina@broadinstitute.org>

See Also

Useful links:

- https://www.borch.dev/uploads/scRepertoire/
- Report bugs at https://github.com/BorchLab/scRepertoire/issues

addVariable *Adding variables after combineTCR() or combineBCR()*

Description

This function adds variables to the product of combineTCR(), or combineBCR() to be used in later visualizations. For each element, the function will add a column (labeled by **variable.name**) with the variable. The length of the **variables** parameter needs to match the length of the combined object.

Usage

```
addVariable(input.data, variable.name = NULL, variables = NULL)
```

Arguments

input.data	The product of combineTCR() or combineBCR().
variable.name	The new column name/header.
variables	The exact values to add to each element of the list.

Value

input.data list with the variable column added to each element.

Examples

```
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
combined <- addVariable(combined,
                        variable.name = "Type",
                        variables = rep(c("B", "L"), 4))
```

alluvialClones *Alluvial plotting for single-cell object meta data*

Description

View the proportional contribution of clones by Seurat or SCE object meta data after combineExpression(). The visualization is based on the ggalluvial package, which requires the aesthetics to be part of the axes that are visualized. Therefore, alpha, facet, and color should be part of the the axes you wish to view or will add an additional stratum/column to the end of the graph.

Usage

```
alluvialClones(
  sc.data,
  cloneCall = "strict",
  chain = "both",
  y.axes = NULL,
  color = NULL,
  alpha = NULL,
  facet = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

sc.data	The single-cell object to visualize after combineExpression().
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
y.axes	The columns that will separate the proportional . visualizations.
color	The column header or clone(s) to be highlighted.
alpha	The column header to have gradated opacity.
facet	The column label to separate.
exportTable	Exports a table of the data into the global environment in addition to the visualization.
palette	Colors to use in visualization - input any hcl.pals.

Value

Alluvial ggplot comparing clone distribution.

Examples

```
#Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

#Getting a sample of a Seurat object
scRep_example <- get(data("scRep_example"))

#Using combineExpresion()
scRep_example <- combineExpression(combined, scRep_example)
scRep_example$Patient <- substring(scRep_example$orig.ident, 1,3)
```

```
#Using alluvialClones()
alluvialClones(scRep_example,
                   cloneCall = "gene",
                   y.axes = c("Patient", "ident"),
                   color = "ident")
```

---

clonalAbundance *Demonstrate the relative abundance of clones by group or sample*

Description

Displays the number of clones at specific frequencies by sample or group. Visualization can either be a line graph (**scale** = FALSE) using calculated numbers or density plot (**scale** = TRUE). Multiple sequencing runs can be group together using the group parameter. If a matrix output for the data is preferred, set **exportTable** = TRUE.

Usage

```
clonalAbundance(
  input.data,
  cloneCall = "strict",
  chain = "both",
  scale = FALSE,
  group.by = NULL,
  order.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL"
scale	Converts the graphs into density plots in order to show relative distributions.
group.by	The variable to use for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
exportTable	Returns the data frame used for forming the graph to the visualization.
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot of the total or relative abundance of clones across quanta

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalAbundance(combined,
                cloneCall = "gene",
                scale = FALSE)
```

`clonalBias` *Examine skew of clones towards a cluster or compartment*

Description

The metric seeks to quantify how individual clones are skewed towards a specific cellular compartment or cluster. A clone bias of **1** - indicates that a clone is composed of cells from a single compartment or cluster, while a clone bias of **0** - matches the background subtype distribution. Please read and cite the following manuscript if using `clonalBias()`.

Usage

```
clonalBias(
  sc.data,
  cloneCall = "strict",
  split.by = NULL,
  group.by = NULL,
  n.boots = 20,
  min.expand = 10,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

`sc.data`	The single-cell object after `combineExpression()`.
`cloneCall`	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
`split.by`	The variable to use for calculating the baseline frequencies. For example, "Type" for lung vs peripheral blood comparison
`group.by`	The variable to use for calculating bias
`n.boots`	number of bootstraps to downsample.
`min.expand`	clone frequency cut off for the purpose of comparison.
`exportTable`	Returns the data frame used for forming the graph.
`palette`	Colors to use in visualization - input any hcl.pals.

Value

ggplot scatter plot with clone bias

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

#Getting a sample of a Seurat object
scRep_example <- get(data("scRep_example"))

#Using combineExpresion()
scRep_example <- combineExpression(combined, scRep_example)
scRep_example$Patient <- substring(scRep_example$orig.ident,1,3)

#Using clonalBias()
clonalBias(scRep_example,
              cloneCall = "aa",
              split.by = "Patient",
              group.by = "seurat_clusters",
              n.boots = 5,
              min.expand = 2)
```

`clonalCluster` *Clustering adaptive receptor sequences by edit distance*

Description

This function uses edit distances of either the nucleotide or amino acid sequences of the CDR3 and V genes to cluster similar TCR/BCRs together. As a default, the function takes the input from `combineTCR()`, `combineBCR()` or `combineExpression()` and amends a cluster to the data frame or meta data. If **exportGraph** is set to TRUE, the function returns an igraph object of the connected sequences. If multiple sequences per chain are present, this function only compares the first sequence.

Usage

```
clonalCluster(
  input.data,
  chain = "TRB",
  sequence = "aa",
  samples = NULL,
  threshold = 0.85,
  group.by = NULL,
  exportGraph = FALSE
)
```

Arguments

input.data	The product of combineTCR(), combineBCR() or combineExpression().
chain	Indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
sequence	Clustering based on either **"aa"** or **"nt"**.
samples	The specific samples to isolate for visualization.
threshold	The normalized edit distance to consider. The higher the number the more similarity of sequence will be used for clustering.
group.by	The column header used for to group contigs. If (**NULL**), clusters will be calculated across samples.
exportGraph	Return an igraph object of connected sequences (**TRUE**) or the amended input with a new cluster-based variable (**FALSE**).

Value

Either amended input with edit-distanced clusters added or igraph object of connect sequences

Examples

```
# Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

sub_combined <- clonalCluster(combined[c(1,2)],
                              chain = "TRA",
                              sequence = "aa")
```

---

clonalCompare *Demonstrate the difference in clonal proportions / counts between clones*

Description

This function produces an alluvial or area graph of the proportion or count composition of the indicated clones for all or selected samples (using the **samples** parameter). Individual clones can be selected using the **clones** parameter with the specific sequence of interest or using the **top.clones** parameter with the top n clones by proportion / counts to be visualized.

Usage

```
clonalCompare(
  input.data,
  cloneCall = "strict",
  chain = "both",
  samples = NULL,
  clones = NULL,
  top.clones = NULL,
  highlight.clones = NULL,
  relabel.clones = FALSE,
  group.by = NULL,
  order.by = NULL,
  graph = "alluvial",
  proportion = TRUE,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR, combineBCR, or combineExpression.
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL"
samples	The specific samples to isolate for visualization.
clones	The specific clonal sequences of interest
top.clones	The top number of clonal sequences per group. (e.g., top.clones = 5)
highlight.clones	Clonal sequences to highlight, if present, all other clones returned will be grey
relabel.clones	Simplify the legend of the graph by returning clones that are numerically indexed
group.by	If using a single-cell object, the column header to group the new list. **NULL** will return the active identity or cluster
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
graph	The type of graph produced, either **"alluvial"** or **"area"**
proportion	If **TRUE**, the proportion of the total sequencing reads will be used for the y-axis. If **FALSE**, the raw count will be used
exportTable	Returns the data frame used for forming the graph
palette	Colors to use in visualization - input any hcl.pals

Value

ggplot of the proportion of total sequencing read of selecting clones

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalCompare(combined,
              top.clones = 5,
              samples = c("P17B", "P17L"),
              cloneCall="aa")
```

`clonalDiversity` *Calculate the clonal diversity for samples or groupings*

Description

This function calculates traditional measures of diversity - **Shannon**, **inverse Simpson**, **normalized entropy**, **Gini-Simpson**, **Chao1 index**, and **abundance-based coverage estimators (ACE)** measure of species evenness by sample or group. The function automatically down samples the diversity metrics using 100 boot straps (**n.boots = 100**) and outputs the mean of the values. The group parameter can be used to condense the individual samples. If a matrix output for the data is preferred, set **exportTable** = TRUE.

Usage

```
clonalDiversity(
  input.data,
  cloneCall = "strict",
  chain = "both",
  group.by = NULL,
  order.by = NULL,
  x.axis = NULL,
 metrics = c("shannon", "inv.simpson", "norm.entropy", "gini.simpson", "chao1", "ACE"),
  exportTable = FALSE,
  palette = "inferno",
  n.boots = 100,
  return.boots = FALSE,
  skip.boots = FALSE
)
```

Arguments

`input.data`	The product of `combineTCR()`, `combineBCR()`, or `combineExpression()`.
`cloneCall`	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data

chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL"
group.by	Variable in which to combine for the diversity calculation
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
x.axis	Additional variable grouping that will space the sample along the x-axis
metrics	The indices to use in diversity calculations - "shannon", "inv.simpson", "norm.entropy", "gini.simpson", "chao1", "ACE"
exportTable	Exports a table of the data into the global environment in addition to the visualization
palette	Colors to use in visualization - input any hcl.pals
n.boots	number of bootstraps to down sample in order to get mean diversity
return.boots	export boot strapped values calculated - will automatically exportTable = TRUE.
skip.boots	remove down sampling and boot strapping from the calculation.

Details

The formulas for the indices and estimators are as follows:

Shannon Index:

$$Index = -\sum p_i * \log(p_i)$$

Inverse Simpson Index:

$$Index = \frac{1}{(\sum_{i=1}^{S} p_i^2)}$$

Normalized Entropy:

$$Index = -\frac{\sum_{i=1}^{S} p_i \ln(p_i)}{\ln(S)}$$

Gini-Simpson Index:

$$Index = 1 - \sum_{i=1}^{S} p_i^2$$

Chao1 Index:

$$Index = S_{obs} + \frac{n_1(n_1 - 1)}{2 * n_2 + 1}$$

Abundance-based Coverage Estimator (ACE):

$$Index = S_{abund} + \frac{S_{rare}}{C_{ace}} + \frac{F_1}{C_{ace}}$$

Where:

- p_i is the proportion of species i in the dataset.
- S is the total number of species.
- n_1 and n_2 are the number of singletons and doubletons, respectively.
- S_{abund}, S_{rare}, C_{ace}, and F_1 are parameters derived from the data.

Value

ggplot of the diversity of clones by group

Author(s)

Andrew Malone, Nick Borcherding

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalDiversity(combined, cloneCall = "gene")
```

---

clonalHomeostasis *Examining the clonal homeostasis of the repertoire*

Description

This function calculates the space occupied by clone proportions. The grouping of these clones is based on the parameter **cloneSize**, at default, **cloneSize** will group the clones into bins of Rare = 0 to 0.0001, Small = 0.0001 to 0.001, etc. To adjust the proportions, change the number or labeling of the cloneSize parameter. If a matrix output for the data is preferred, set **exportTable** = TRUE.

Usage

```
clonalHomeostasis(
  input.data,
 cloneSize = c(Rare = 1e-04, Small = 0.001, Medium = 0.01, Large = 0.1, Hyperexpanded =
    1),
  cloneCall = "strict",
  chain = "both",
  group.by = NULL,
  order.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
cloneSize	The cut points of the proportions.
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.

chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
group.by	The variable to use for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
exportTable	Exports a table of the data into the global environment in addition to the visualization.
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot of the space occupied by the specific proportion of clones

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalHomeostasis(combined, cloneCall = "gene")
```

---

clonalLength *Demonstrate the distribution of clonal length*

Description

This function displays either the nucleotide (**nt**) or amino acid (**aa**) sequence length. The sequence length visualized can be selected using the chains parameter, either the combined clone (both chains) or across all single chains. Visualization can either be a histogram or if **scale** = TRUE, the output will be a density plot. Multiple sequencing runs can be group together using the group.by parameter.

Usage

```
clonalLength(
  input.data,
  cloneCall = "aa",
  chain = "both",
  group.by = NULL,
  order.by = NULL,
  scale = FALSE,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression()
cloneCall	How to call the clone - CDR3 nucleotide (**nt**) or CDR3 amino acid (**aa**)
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL"
group.by	The variable to use for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order description
scale	Converts the graphs into density plots in order to show relative distributions.
exportTable	Returns the data frame used for forming the graph.
palette	Colors to use in visualization - input any hcl.pals

Value

ggplot of the discrete or relative length distributions of clone sequences

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalLength(combined, cloneCall="aa", chain = "both")
```

---

clonalNetwork *Visualize clonal network along reduced dimensions*

Description

This function generates a network based on clonal proportions of an indicated identity and then superimposes the network onto a single-cell object dimensional reduction plot.

Usage

```
clonalNetwork(
  sc.data,
  reduction = "umap",
  group.by = "ident",
  filter.clones = NULL,
  filter.identity = NULL,
  filter.proportion = NULL,
  filter.graph = FALSE,
  cloneCall = "strict",
  chain = "both",
```

```
  exportClones = FALSE,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

sc.data	The single-cell object after combineExpression().
reduction	The name of the dimensional reduction of the single-cell object.
group.by	The variable to use for the nodes.
filter.clones	Use to select the top n clones (e.g., **filter.clones** = 2000) or n of clones based on the minimum number of all the comparators (e.g., **filter.clone** = "min").
filter.identity	Display the network for a specific level of the indicated identity.
filter.proportion	Remove clones from the network below a specific proportion.
filter.graph	Remove the reciprocal edges from the half of the graph, allowing for cleaner visualization.
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
exportClones	Exports a table of clones that are shared across multiple identity groups and ordered by the total number of clone copies.
exportTable	Exports a table of the data into the global
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot object

Examples

```
## Not run:
#Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

#Getting a sample of a Seurat object
scRep_example  <- get(data("scRep_example"))

#Using combineExpresion()
scRep_example  <- combineExpression(combined, scRep_example)

#Using clonalNetwork()
```

```
clonalNetwork(scRep_example,
              reduction = "umap",
              group.by = "seurat_clusters")

## End(Not run)
```

---

clonalOccupy *Visualize the number of single cells with cloneSizes by cluster*

Description

View the count of clones frequency group in Seurat or SCE object meta data after `combineExpression()`. The visualization will take the new meta data variable **"cloneSize"** and plot the number of cells with each designation using a secondary variable, like cluster. Credit to the idea goes to Drs. Carmona and Andreatta and their work with ProjectTIL.

Usage

```
clonalOccupy(
  sc.data,
  x.axis = "ident",
  label = TRUE,
  facet.by = NULL,
  order.by = NULL,
  proportion = FALSE,
  na.include = FALSE,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

`sc.data`	The single-cell object after `combineExpression()`
`x.axis`	The variable in the meta data to graph along the x.axis.
`label`	Include the number of clone in each category by x.axis variable
`facet.by`	The column header used for faceting the graph
`order.by`	A vector of specific plotting order or "alphanumeric" to plot groups in order description
`proportion`	Convert the stacked bars into relative proportion
`na.include`	Visualize NA values or not
`exportTable`	Exports a table of the data into the global environment in addition to the visualization
`palette`	Colors to use in visualization - input any hcl.pals

Value

Stacked bar plot of counts of cells by clone frequency group

Examples

```
#Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

#Getting a sample of a Seurat object
scRep_example <- get(data("scRep_example"))

#Using combineExpresion()
scRep_example <- combineExpression(combined, scRep_example)

#Using clonalOccupy
clonalOccupy(scRep_example, x.axis = "ident")
table <- clonalOccupy(scRep_example, x.axis = "ident", exportTable = TRUE)
```

---

clonalOverlap *Examining the clonal overlap between groups or samples*

Description

This functions allows for the calculation and visualizations of various overlap metrics for clones. The methods include overlap coefficient (**overlap**), Morisita's overlap index (**morisita**), Jaccard index (**jaccard**), cosine similarity (**cosine**) or the exact number of clonal overlap (**raw**).

Usage

```
clonalOverlap(
  input.data,
  cloneCall = "strict",
  method = NULL,
  chain = "both",
  group.by = NULL,
  order.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression()

`cloneCall`	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data
`method`	The method to calculate the "overlap", "morisita", "jaccard", "cosine" indices or "raw" for the base numbers
`chain`	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL"
`group.by`	The variable to use for grouping
`order.by`	A vector of specific plotting order or "alphanumeric" to plot groups in order
`exportTable`	Returns the data frame used for forming the graph
`palette`	Colors to use in visualization - input any hcl.pals

Details

The formulas for the indices are as follows:

Overlap Coefficient:

$$overlap = \frac{\sum \min(a, b)}{\min(\sum a, \sum b)}$$

Raw Count Overlap:

$$raw = \sum \min(a, b)$$

Morisita Index:

$$morisita = \frac{\sum ab}{(\sum a)(\sum b)}$$

Jaccard Index:

$$jaccard = \frac{\sum \min(a, b)}{\sum a + \sum b - \sum \min(a, b)}$$

Cosine Similarity:

$$cosine = \frac{\sum ab}{\sqrt{(\sum a^2)(\sum b^2)}}$$

Where:

- a and b are the abundances of species i in groups A and B, respectively.

Value

ggplot of the overlap of clones by group

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

clonalOverlap(combined,
              cloneCall = "aa",
              method = "jaccard")
```

`clonalOverlay` *Visualize distribution of clonal frequency overlaid on dimensional reduction plots*

Description

This function allows the user to visualize the clonal expansion by overlaying the cells with specific clonal frequency onto the dimensional reduction plots in Seurat. Credit to the idea goes to Drs Andreatta and Carmona and their work with ProjectTIL.

Usage

```
clonalOverlay(
  sc.data,
  reduction = NULL,
  cut.category = "clonalFrequency",
  cutpoint = 30,
  bins = 25,
  facet.by = NULL
)
```

Arguments

`sc.data`	The single-cell object after `combineExpression()`.
`reduction`	The dimensional reduction to visualize.
`cut.category`	Meta data variable of the single-cell object to use for filtering.
`cutpoint`	The overlay cut point to include, this corresponds to the cut.category variable in the meta data of the single-cell object.
`bins`	The number of contours to the overlay
`facet.by`	meta data variable to facet the comparison

Value

ggplot object

Author(s)

Francesco Mazziotta, Nick Borcherding

Examples

```
#Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
#Getting a sample of a Seurat object
scRep_example <- get(data("scRep_example"))

#Using combineExpresion()
scRep_example <- combineExpression(combined,
                                   scRep_example)

#Using clonalOverlay()
clonalOverlay(scRep_example,
              reduction = "umap",
              cutpoint = 3,
              bins = 5)
```

---

clonalProportion *Examining the clonal space occupied by specific clones*

Description

This function calculates the relative clonal space occupied by the clones. The grouping of these clones is based on the parameter **clonalSplit**, at default, **clonalSplit** will group the clones into bins of 1:10, 11:100, 101:1001, etc. To adjust the clones selected, change the numbers in the variable split. If a matrix output for the data is preferred, set **exportTable** = TRUE.

Usage

```
clonalProportion(
  input.data,
  clonalSplit = c(10, 100, 1000, 10000, 30000, 1e+05),
  cloneCall = "strict",
  chain = "both",
  group.by = NULL,
  order.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
clonalSplit	The cut points for the specific clones
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL"
group.by	The variable to use for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
exportTable	Exports a table of the data into the global. environment in addition to the visualization
palette	Colors to use in visualization - input any hcl.pals

Value

ggplot of the space occupied by the specific rank of clones

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalProportion(combined, cloneCall = "gene")
```

---

clonalQuant *Quantify the unique clones by group or sample*

Description

This function quantifies unique clones. The unique clones can be either reported as a raw output or scaled to the total number of clones recovered using the scale parameter.

Usage

```
clonalQuant(
  input.data,
  cloneCall = "strict",
  chain = "both",
  scale = FALSE,
  group.by = NULL,
  order.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL"
scale	Converts the graphs into percentage of unique clones
group.by	The column header used for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
exportTable	Returns the data frame used for forming the graph
palette	Colors to use in visualization - input any hcl.pals

Value

ggplot of the total or relative unique clones

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalQuant(combined,
            cloneCall="strict",
            scale = TRUE)
```

---

clonalRarefaction *Calculate rarefaction based on the abundance of clones*

Description

This functions uses the Hill numbers of order q: species richness (**q = 0**), Shannon diversity (**q = 1**), the exponential of Shannon entropy and Simpson diversity (**q = 2**, the inverse of Simpson concentration) to compute diversity estimates for rarefaction and extrapolation. The function relies on the iNEXT::iNEXT() R package. Please read and cite the manuscript if using this function. The input into the iNEXT calculation is abundance, incidence-based calculations are not supported.

Usage

```
clonalRarefaction(
  input.data,
  cloneCall = "strict",
  chain = "both",
```

```
  group.by = NULL,
  plot.type = 1,
  hill.numbers = 0,
  n.boots = 20,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
group.by	The variable to use for grouping.
plot.type	sample-size-based rarefaction/extrapolation curve (type = 1); sample completeness curve (type = 2); coverage-based rarefaction/extrapolation curve (type = 3).
hill.numbers	The Hill numbers to be plotted out (0 - species richness, 1 - Shannon, 2 - Simpson)
n.boots	The number of bootstraps to downsample in order to get mean diversity.
exportTable	Exports a table of the data into the global environment in addition to the visualization.
palette	Colors to use in visualization - input any hcl.pals.

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalRarefaction(combined[c(1,2)], cloneCall = "gene", n.boots = 3)
```

---

clonalScatter *Scatter plot comparing the clonal expansion of two samples*

Description

This function produces a scatter plot directly comparing the specific clones between two samples. The clones will be categorized by counts into singlets or expanded, either exclusive or shared between the selected samples.

Usage

```
clonalScatter(
  input.data,
  cloneCall = "strict",
  x.axis = NULL,
  y.axis = NULL,
  chain = "both",
  dot.size = "total",
  group.by = NULL,
  graph = "proportion",
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
x.axis	name of the list element to appear on the x.axis.
y.axis	name of the list element to appear on the y.axis.
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
dot.size	either total or the name of the list element to use for size of dots.
group.by	The variable to use for grouping.
graph	graph either the clonal "proportion" or "count".
exportTable	Returns the data frame used for forming the graph.
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot of the relative clone numbers between two sequencing runs or groups

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalScatter(combined,
              x.axis = "P17B",
              y.axis = "P17L",
              graph = "proportion")
```

`clonalSizeDistribution` *Hierarchical clustering of clones using Gamma-GPD spliced threshold model*

Description

This function produces a hierarchical clustering of clones by sample using discrete gamma-GPD spliced threshold model. If using this model please read and cite powerTCR (more info available at PMID: 30485278).

Usage

```
clonalSizeDistribution(
  input.data,
  cloneCall = "strict",
  chain = "both",
  method = "ward.D2",
  threshold = 1,
  group.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

`input.data`	The product of `combineTCR()`, `combineBCR()`, or `combineExpression()`.
`cloneCall`	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
`chain`	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
`method`	The clustering parameter for the dendrogram.
`threshold`	Numerical vector containing the thresholds the grid search was performed over.
`group.by`	The variable to use for grouping.
`exportTable`	Returns the data frame used for forming the graph.
`palette`	Colors to use in visualization - input any hcl.pals.

Details

The probability density function (pdf) for the **Generalized Pareto Distribution (GPD)** is given by:

$$f(x|\mu,\sigma,\xi) = \frac{1}{\sigma}\left(1+\xi\left(\frac{x-\mu}{\sigma}\right)\right)^{-\left(\frac{1}{\xi}+1\right)}$$

Where:

- μ is a location parameter
- $\sigma > 0$ is a scale parameter
- ξ is a shape parameter
- $x \geq \mu$ if $\xi \geq 0$ and $\mu \leq x \leq \mu - \sigma/\xi$ if $\xi < 0$

The probability density function (pdf) for the **Gamma Distribution** is given by:

$$f(x|\alpha, \beta) = \frac{x^{\alpha-1}e^{-x/\beta}}{\beta^{\alpha}\Gamma(\alpha)}$$

Where:

- $\alpha > 0$ is the shape parameter
- $\beta > 0$ is the scale parameter
- $x \geq 0$
- $\Gamma(\alpha)$ is the gamma function of α

Value

ggplot dendrogram of the clone size distribution

Author(s)

Hillary Koch

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
clonalSizeDistribution(combined, cloneCall = "strict", method="ward.D2")
```

---

combineBCR *Combining the list of B cell receptor contigs into clones*

Description

This function consolidates a list of BCR sequencing results to the level of the individual cell barcodes. Using the samples and ID parameters, the function will add the strings as prefixes to prevent issues with repeated barcodes. The resulting new barcodes will need to match the Seurat or SCE object in order to use, `combineExpression()`. Unlike `combineTCR()`, combineBCR produces a column **CTstrict** of an index of nucleotide sequence and the corresponding V gene. This index automatically calculates the Levenshtein distance between sequences with the same V gene and will index sequences using a normalized Levenshtein distance with the same ID. After which, clone clusters are called using the `igraph::components()` function. Clones that are clustered across multiple sequences will then be labeled with "Cluster" in the CTstrict header.

Usage

```
combineBCR(
  input.data,
  samples = NULL,
  ID = NULL,
  call.related.clones = TRUE,
  threshold = 0.85,
  removeNA = FALSE,
  removeMulti = FALSE,
  filterMulti = TRUE,
  filterNonproductive = TRUE
)
```

Arguments

input.data	List of filtered contig annotations or outputs from loadContigs().
samples	The labels of samples (required).
ID	The additional sample labeling (optional).
call.related.clones	Use the nucleotide sequence and V gene to call related clones. Default is set to TRUE. FALSE will return a CTstrict or strict clone as V gene + amino acid sequence.
threshold	The normalized edit distance to consider. The higher the number the more similarity of sequence will be used for clustering.
removeNA	This will remove any chain without values.
removeMulti	This will remove barcodes with greater than 2 chains.
filterMulti	This option will allow for the selection of the highest-expressing light and heavy chains, if not calling related clones.
filterNonproductive	This option will allow for the removal of nonproductive chains if the variable exists in the contig data. Default is set to TRUE to remove nonproductive contigs.

Value

List of clones for individual cell barcodes

Examples

```
#Data derived from the 10x Genomics intratumoral NSCLC B cells
BCR <- read.csv("https://www.borch.dev/uploads/contigs/b_contigs.csv")
combined <- combineBCR(BCR,
                       samples = "Patient1",
                       threshold = 0.85)
```

combineExpression *Adding clone information to a single-cell object*

Description

This function adds the immune receptor information to the Seurat or SCE object to the meta data. By default this function also calculates the frequencies and proportion of the clones by sequencing run (**group.by** = NULL). To change how the frequencies/proportions are calculated, select a column header for the **group.by** variable. Importantly, before using `combineExpression()` ensure the barcodes of the single-cell object object match the barcodes in the output of the `combineTCR()` or `combineBCR()`.

Usage

```
combineExpression(
  input.data,
  sc.data,
  cloneCall = "strict",
  chain = "both",
  group.by = NULL,
  proportion = TRUE,
  filterNA = FALSE,
 cloneSize = c(Rare = 1e-04, Small = 0.001, Medium = 0.01, Large = 0.1, Hyperexpanded =
    1),
  addLabel = FALSE
)
```

Arguments

input.data	The product of `combineTCR()`, `combineBCR()` or a list of both c(`combineTCR()`, `combineBCR()`).
sc.data	The Seurat or Single-Cell Experiment (SCE) object to attach
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
group.by	The column label in the combined clones in which clone frequency will be calculated. **NULL** or **"none"** will keep the format of input.data.
proportion	Whether to proportion (**TRUE**) or total frequency (**FALSE**) of the clone based on the group.by variable.
filterNA	Method to subset Seurat/SCE object of barcodes without clone information
cloneSize	The bins for the grouping based on proportion or frequency. If proportion is **FALSE** and the cloneSizes are not set high enough based on frequency, the upper limit of cloneSizes will be automatically updated.S

addLabel This will add a label to the frequency header, allowing the user to try multiple group.by variables or recalculate frequencies after subsetting the data.

Value

Single-cell object with clone information added to meta data information

Examples

```
#Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

#Getting a sample of a Seurat object
scRep_example <- get(data("scRep_example"))

#Using combineExpresion()
scRep_example <- combineExpression(combined, scRep_example)
```

---

combineTCR *Combining the list of T cell receptor contigs into clones*

Description

This function consolidates a list of TCR sequencing results to the level of the individual cell barcodes. Using the **samples** and **ID** parameters, the function will add the strings as prefixes to prevent issues with repeated barcodes. The resulting new barcodes will need to match the Seurat or SCE object in order to use, `combineExpression()`. Several levels of filtering exist - *removeNA*, *removeMulti*, or *filterMulti* are parameters that control how the function deals with barcodes with multiple chains recovered.

Usage

```
combineTCR(
  input.data,
  samples = NULL,
  ID = NULL,
  removeNA = FALSE,
  removeMulti = FALSE,
  filterMulti = FALSE,
  filterNonproductive = TRUE
)
```

Arguments

input.data	List of filtered contig annotations or outputs from loadContigs().
samples	The labels of samples (recommended).
ID	The additional sample labeling (optional).
removeNA	This will remove any chain without values.
removeMulti	This will remove barcodes with greater than 2 chains.
filterMulti	This option will allow for the selection of the 2 corresponding chains with the highest expression for a single barcode.
filterNonproductive	This option will allow for the removal of nonproductive chains if the variable exists in the contig data. Default is set to TRUE to remove nonproductive contigs.

Value

List of clones for individual cell barcodes

Examples

```
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
```

---

contig_list *A list of 8 single-cell T cell receptor sequences runs.*

Description

A list of 8 filtered_contig_annotations.csv files outputted from 10X Cell Ranger. More information on the data can be found in the following manuscript.

---

createHTOContigList *Generate a contig list from a multiplexed experiment*

Description

This function reprocess and forms a list of contigs for downstream analysis in scRepertoire, createHTOContigList() take the filtered contig annotation output and the single-cell RNA object to create the list. If using an integrated single-cell object, it is recommended to split the object by sequencing run and remove extra prefixes and suffixes on the barcode before using createHTOContigList(). Alternatively, the variable **multi.run** can be used to separate a list of contigs by a meta data variable. This may have issues with the repeated barcodes.

Usage

```
createHTOContigList(contig, sc.data, group.by = NULL, multi.run = NULL)
```

Arguments

contig	The filtered contig annotation file from multiplexed experiment
sc.data	The Seurat or Single-Cell Experiment object.
group.by	One or more meta data headers to create the contig list based on. If more than one header listed, the function combines them into a single variable.
multi.run	If using integrated single-cell object, the meta data variable that indicates the sequencing run.

Value

Returns a list of contigs as input for combineBCR() or combineTCR()

Examples

```
## Not run:
filtered.contig <- read.csv(".../Sample/outs/filtered_contig_annotations.csv")

contig.list <- createHTOContigList(contig = filtered.contig,
                                   sc.data = Seurat.Obj,
                                   group.by = "HTO_maxID")

## End(Not run)
```

---

exportClones *Exporting clones*

Description

This function saves a csv file of clones (genes, amino acid, and nucleotide sequences) by barcodes. **format** determines the structure of the csv file - *paired* will export sequences by barcodes and include multiple chains, *airr* will export a data frame that is consistent with the AIRR format, and *TCRMatch* will export a data frame that has the TRB chain with count information.

Usage

```
exportClones(
  input.data,
  format = "paired",
  group.by = NULL,
  write.file = TRUE,
  dir = NULL,
  file.name = "clones.csv"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
format	The format to export the clones - "paired", "airr", or "TCRMatch".
group.by	The variable to use for grouping.
write.file	**TRUE**, save the file or **FALSE**, return a data.frame
dir	directory location to save the csv
file.name	the csv file name

Value

CSV file of the paired sequences.

Author(s)

Jonathan Noonan, Nick Borcherding

Examples

```
## Not run:
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
exportClones(combined,
             format = "paired")

## End(Not run)
```

---

expression2List — **DEPRECATED** *Take the meta data in seurat/SCE and place it into a list*

Description

[Deprecated]

Allows users to perform more fundamental measures of clonotype analysis using the meta data from the seurat or SCE object. For Seurat objects the active identity is automatically added as "cluster". Remaining grouping parameters or SCE or Seurat objects must appear in the meta data.

This function is deprecated as of version 2 due to the confusion it caused to many users. Users are encouraged to remain with the abstraction barrier of combined single cell objects and the outputs of combineTCR() and combineBCR() for all functions.

We discourage the use of this function, but if you have to use it, set the force argument to TRUE.

Usage

```
expression2List(sc, ..., force = FALSE)
```

Arguments

sc	output of combineExpression().
...	previously the group or split.by argument, indicating the column header to group the new list by. This should strictly be one argument and is an ellipsis for backwards compatibility. Everything after the first argument is ignored.
force	logical. If not TRUE (default), a deprecation error will be thrown. Otherwise the function will run but not guaranteed to be stable.

Value

list derived from the meta data of single-cell object with elements divided by the group parameter

---

getCirclize *Generate data frame to be used with circlize R package to visualize clones as a chord diagram.*

Description

This function will take the meta data from the product of combineExpression() and generate a relational data frame to be used for a chord diagram. Each cord will represent the number of clone unique and shared across the multiple **group.by** variable. If using the downstream circlize R package, please read and cite the following manuscript. If looking for more advance ways for circular visualizations, there is a great cookbook for the circlize package.

Usage

```
getCirclize(
  sc.data,
  cloneCall = "strict",
  group.by = NULL,
  proportion = FALSE,
  include.self = TRUE
)
```

Arguments

sc.data	The single-cell object after combineExpression().
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
group.by	The group header for which you would like to analyze the data.
proportion	Calculate the relationship unique clones (proportion = FALSE) or normalized by proportion (proportion = TRUE)
include.self	Include counting the clones within a single group.by comparison

Value

A data frame of shared clones between groups formated for chordDiagram

Author(s)

Dillon Corvino, Nick Borcherding

Examples

```
#Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

#Getting a sample of a Seurat object
scRep_example <- get(data("scRep_example"))
scRep_example <- combineExpression(combined,
                                   scRep_example)

#Getting data frame output for Circlize
circles <- getCirclize(scRep_example,
                       group.by = "seurat_clusters")
```

---

getContigDoublets *Get Contig Doublets*

Description

[Experimental]

This function identifies potential doublets by finding common barcodes between TCR and BCR outputs. It extracts unique barcodes from each list of dataframes, finds the intersection of the barcodes, and joins the resulting data.

Usage

```
getContigDoublets(tcrOutput, bcrOutput)
```

Arguments

tcrOutput	Output of combineTCR(). A list of data.frames containing TCR contig information, each dataframe must have a barcode column.
bcrOutput	Output of combineBCR(). A list of data.frames containing BCR contig information, each dataframe must have a barcode column.

Value

A dataframe of barcodes that exist in both the TCR and BCR data, with columns from both sets of data. There will be an additional column `contigType` of type factor with levels 'TCR' and 'BCR' indicating the origin of the contig - this will be the new first column.

If there are no doublets, the returned data.frame will have the same colnames but no rows.

`getHumanIgPseudoGenes` *Get Human Immunoglobulin pseudogenes*

Description

This function returns a character vector of human immunoglobulin pseudogenes. These are also the genes that are removed from the variable gene list in `quietVDJgenes()`.

Usage

```
getHumanIgPseudoGenes()
```

Value

Character vector of human immunoglobulin pseudogenes.

`highlightClones` *Highlighting specific clones in Seurat*

Description

Use a specific clonal sequence to highlight on top of the dimensional reduction in single-cell object.

Usage

```
highlightClones(
  sc.data,
  cloneCall = c("gene", "nt", "aa", "strict"),
  sequence = NULL
)
```

Arguments

`sc.data`	The single-cell object to attach after `combineExpression()`
`cloneCall`	How to call the clone - VDJC gene (gene), CDR3 nucleotide (nt), CDR3 amino acid (aa), VDJC gene + CDR3 nucleotide (strict) or a custom variable in the data.
`sequence`	The specific sequence or sequence to highlight

Value

Single-cell object object with new meta data column for indicated clones

Examples

```
#Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

#Getting a sample of a Seurat object
scRep_example  <- get(data("scRep_example"))

#Using combineExpresion()
scRep_example  <- combineExpression(combined,
                                    scRep_example)

#Using highlightClones()
scRep_example   <- highlightClones(scRep_example,
                                   cloneCall= "aa",
                                   sequence = c("CVVSDNTGGFKTIF_CASSVRRERANTGELFF"))
```

---

loadContigs *Loading the contigs derived from single-cell sequencing*

Description

This function generates a contig list and formats the data to allow for function with `combineTCR()` or `combineBCR()`. If using data derived from filtered outputs of 10X Genomics, there is no need to use this function as the data is already compatible.

The files that this function parses includes:

- **10X**: `"filtered_contig_annotations.csv"`
- **AIRR**: `"airr_rearrangement.tsv"`
- **BD**: `"Contigs_AIRR.tsv"`
- **Dandelion**: `"all_contig_dandelion.tsv"`
- **Immcantation**: `"data.tsv"`
- **JSON**: `".json"`
- **ParseBio**: `"barcode_report.tsv"`
- **MiXCR**: `"clones.tsv"`
- **Omniscope**: `".csv"`
- **TRUST4**: `"barcode_report.tsv"`
- **WAT3R**: `"barcode_results.csv"`

Usage

```
loadContigs(input, format = "10X")
```

Arguments

input	The directory in which contigs are located or a list with contig elements
format	The format of the single-cell contig, currently supporting: "10X", "AIRR", "BD", "Dandelion", "JSON", "MiXCR", "ParseBio", "Omniscope", "TRUST4", "WAT3R", and "Immcantation"

Value

List of contigs for compatibility with `combineTCR()` or `combineBCR()`. Note that rows which are fully NA are dropped from the final output.

Examples

```
TRUST4 <- read.csv("https://www.borch.dev/uploads/contigs/TRUST4_contigs.csv")
contig.list <- loadContigs(TRUST4, format = "TRUST4")

BD <- read.csv("https://www.borch.dev/uploads/contigs/BD_contigs.csv")
contig.list <- loadContigs(BD, format = "BD")

WAT3R <- read.csv("https://www.borch.dev/uploads/contigs/WAT3R_contigs.csv")
contig.list <- loadContigs(WAT3R, format = "WAT3R")
```

---

mini_contig_list *Processed subset of* contig_list

Description

A list of 8 data frames of T cell contigs outputted from the `filtered_contig_annotation` files, but subsetted to 365 valid T cells which correspond to the same barcodes found in `scRep_example`. The data is originally derived from the following manuscript.

Usage

```
data("mini_contig_list")
```

Format

An R `list` of `data.frame` objects

See Also

`contig_list()`

percentAA *Examining the relative amino acid composition by position*

Description

This function the proportion of amino acids along the residues of the CDR3 amino acid sequence.

Usage

```
percentAA(
  input.data,
  chain = "TRB",
  group.by = NULL,
  order.by = NULL,
  aa.length = 20,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
chain	"TRA", "TRB", "TRG", "TRG", "IGH", "IGL".
group.by	The variable to use for grouping.
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
aa.length	The maximum length of the CDR3 amino acid sequence.
exportTable	Returns the data frame used for forming the graph.
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot of stacked bar graphs of amino acid proportions

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
percentAA(combined,
          chain = "TRB",
          aa.length = 20)
```

percentGenes *Examining the VDJ gene usage across clones*

Description

This function the proportion V or J genes used by grouping variables. This function only quantifies single gene loci for indicated **chain**. For examining VJ pairing, please see `percentVJ()`.

Usage

```
percentGenes(
  input.data,
  chain = "TRB",
  gene = "Vgene",
  group.by = NULL,
  order.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of `combineTCR()`, `combineBCR()`, or `combineExpression()`.
chain	"TRA", "TRB", "TRG", "TRG", "IGH", "IGL".
gene	"V", "D" or "J"
group.by	The variable to use for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
exportTable	Returns the data frame used for forming the graph.
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot of percentage of indicated genes as a heatmap

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
percentGenes(combined,
             chain = "TRB",
             gene = "Vgene")
```

percentKmer *Examining the relative composition of kmer motifs in clones.*

Description

This function the of kmer for nucleotide (**nt**) or amino acid (**aa**) sequences. Select the length of the kmer to quantify using the **motif.length** parameter.

Usage

```
percentKmer(
  input.data,
  chain = "TRB",
  cloneCall = "aa",
  group.by = NULL,
  order.by = NULL,
  motif.length = 3,
  top.motifs = 30,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression()
chain	"TRA", "TRB", "TRG", "TRG", "IGH", "IGL"
cloneCall	How to call the clone - CDR3 nucleotide (**nt**) or CDR3 amino acid (**aa**)
group.by	The variable to use for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
motif.length	The length of the kmer to analyze
top.motifs	Return the n most variable motifs as a function of median absolute deviation
exportTable	Returns the data frame used for forming the graph.
palette	Colors to use in visualization - input any hcl.pals

Value

ggplot of percentage of kmers as a heatmap

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
percentKmer(combined,
```

```
              chain = "TRB",
              motif.length = 3)
```

---

percentVJ *Quantifying the V and J gene usage across clones*

Description

This function the proportion V and J genes used by grouping variables for an indicated **chain** to produce a matrix of VJ gene pairings.

Usage

```
percentVJ(
  input.data,
  chain = "TRB",
  group.by = NULL,
  order.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
chain	"TRA", "TRB", "TRG", "TRG", "IGH", "IGL"
group.by	The variable to use for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
exportTable	Returns the data frame used for forming the graph
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot of percentage of V and J gene pairings as a heatmap

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
percentVJ(combined, chain = "TRB")
```

positionalEntropy *Examining the diversity of amino acids by position*

Description

This function the diversity amino acids along the residues of the CDR3 amino acid sequence. Please see clonalDiversity() for more information on the underlying methods for diversity/entropy calculations. Positions without variance will have a value reported as 0 for the purposes of comparison.

Usage

```
positionalEntropy(
  input.data,
  chain = "TRB",
  group.by = NULL,
  order.by = NULL,
  aa.length = 20,
  method = "norm.entropy",
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression()
chain	"TRA", "TRB", "TRG", "TRG", "IGH", "IGL"
group.by	The variable to use for grouping
order.by	A vector of specific plotting order or "alphanumeric" to plot groups in order
aa.length	The maximum length of the CDR3 amino acid sequence.
method	The method to calculate the entropy/diversity - "shannon", "inv.simpson", "norm.entropy"
exportTable	Returns the data frame used for forming the graph
palette	Colors to use in visualization - input any hcl.pals

Value

ggplot of line graph of diversity by position

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
positionalEntropy(combined,
                  chain = "TRB",
                  aa.length = 20)
```

`positionalProperty` *Examining the mean property of amino acids by position*

Description

This function calculates the mean selected property for amino acids along the residues of the CDR3 amino acid sequence. The ribbon surrounding the individual line represents the 95% confidence interval.

Usage

```
positionalProperty(
  input.data,
  chain = "TRB",
  group.by = NULL,
  order.by = NULL,
  aa.length = 20,
  method = "Atchley",
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

`input.data`	The product of `combineTCR()`, `combineBCR()`, or `combineExpression()`
`chain`	"TRA", "TRB", "TRG", "TRG", "IGH", "IGL"
`group.by`	The variable to use for grouping
`order.by`	A vector of specific plotting order or "alphanumeric" to plot groups in order
`aa.length`	The maximum length of the CDR3 amino acid sequence.
`method`	The method to calculate the property - "Atchley", "Kidera", "stScales", "tScales", or "VHSE"
`exportTable`	Returns the data frame used for forming the graph
`palette`	Colors to use in visualization - input any hcl.pals

Details

More information for the individual methods can be found at the following citations:

Atchley: citation

Kidera: citation

stScales: citation

tScales: citation

VHSE: citation

Value

ggplot of line graph of diversity by position

Author(s)

Florian Bach, Nick Borcherding

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
positionalProperty(combined,
                   chain = "TRB",
                   method = "Atchley",
                   aa.length = 20)
```

`quietVDJgenes` *Remove TCR and BCR genes from variable gene results*

Description

[Experimental]

Most single-cell workflows use highly-expressed and highly-variable genes for the initial calculation of PCA and subsequent dimensional reduction. This function will remove the TCR and/or BCR genes from the variable features in a Seurat object or from a vector (potentially generated by the Bioconductor scran workflow).

Usage

```
quietVDJgenes(sc, ...)

quietTCRgenes(sc, ...)

## Default S3 method:
quietTCRgenes(sc, ...)

## S3 method for class 'Seurat'
quietTCRgenes(sc, assay = NULL, ...)

quietBCRgenes(sc, ...)

## Default S3 method:
quietBCRgenes(sc, ...)

## S3 method for class 'Seurat'
quietBCRgenes(sc, assay = NULL, ...)
```

Arguments

sc	Single-cell object in Seurat format or vector of variable genes to use in reduction
...	Reserved for future arguments
assay	The Seurat assay slot to use to remove immune receptor genes from, NULL value will default to the default assay

Value

Seurat object or vector list with TCR genes removed.

Author(s)

Nicky de Vrij, Nikolaj Pagh, Nick Borcherding, Qile Yang

Examples

```
example <- quietVDJgenes(scRep_example)
trex_example <- quietTCRgenes(scRep_example)
ibex_example <- quietBCRgenes(scRep_example)
```

---

scRep_example *A Seurat object of 500 single T cells,*

Description

The object is compatible with `contig_list` and the TCR sequencing data can be added with `combineExpression`. The data is from 4 patients with acute respiratory distress, with samples taken from both the lung and peripheral blood. More information on the data can be found in the following manuscript.

StartracDiversity *Startrac-based diversity indices for single-cell RNA-seq*

Description

This function utilizes the Startrac approach derived from PMID: 30479382. Required to run the function, the "type" variable needs to include the difference in where the cells were derived. The output of this function will produce 3 indices: **expa** (clonal expansion), **migra** (cross-tissue migration), and **trans** (state transition). In order to understand the underlying analyses of the outputs please read and cite the linked manuscript.

Usage

```
StartracDiversity(
  sc.data,
  cloneCall = "strict",
  chain = "both",
  type = NULL,
  group.by = NULL,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

sc.data	The single-cell object after combineExpression(). For SCE objects, the cluster variable must be in the meta data under "cluster".
cloneCall	How to call the clone - VDJC gene (**gene**), CDR3 nucleotide (**nt**), CDR3 amino acid (**aa**), VDJC gene + CDR3 nucleotide (**strict**) or a custom variable in the data.
chain	indicate if both or a specific chain should be used - e.g. "both", "TRA", "TRG", "IGH", "IGL".
type	The variable in the meta data that provides tissue type.
group.by	The variable in the meta data to group by, often samples.
exportTable	Returns the data frame used for forming the graph.
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot object of Startrac diversity metrics

Author(s)

Liangtao Zheng

Examples

```
#Getting the combined contigs
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

#Getting a sample of a Seurat object
scRep_example  <- get(data("scRep_example"))
scRep_example  <- combineExpression(combined, scRep_example)
scRep_example$Patient <- substring(scRep_example$orig.ident,1,3)
scRep_example$Type <- substring(scRep_example$orig.ident,4,4)

#Using StartracDiversity()
StartracDiversity(scRep_example,
```

```
                type = "Type",
                group.by = "Patient")
```

`subsetClones` *Subset the product of combineTCR() or combineBCR()*

Description

This function allows for the subsetting of the product of `combineTCR()` or `combineBCR()` by the name of the individual list element.

Usage

```
subsetClones(input.data, name, variables = NULL)
```

Arguments

`input.data`	The product of `combineTCR()` or `combineBCR()`.
`name`	The column header/name to use for subsetting.
`variables`	The values to subset by, must be in the names(input.data).

Value

list of contigs that have been filtered for the name parameter

Examples

```
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))
subset <- subsetClones(combined, name = "sample", variables = c("P17B"))
```

`vizGenes` *Visualizing the distribution of gene usage*

Description

This function will allow for the visualizing the distribution of the any VDJ and C gene of the TCR or BCR using heatmap or bar chart. This function requires assumes two chains were used in defining clone, if not, it will default to the only chain present regardless of the chain parameter.

Usage

```
vizGenes(
  input.data,
  x.axis = "TRBV",
  y.axis = NULL,
  group.by = NULL,
  plot = "heatmap",
  order = "gene",
  scale = TRUE,
  exportTable = FALSE,
  palette = "inferno"
)
```

Arguments

input.data	The product of combineTCR(), combineBCR(), or combineExpression().
x.axis	Gene segments to separate the x-axis, such as "TRAV", "TRBD", "IGKJ".
y.axis	Variable to separate the y-axis, can be both categorical or other gene gene segments, such as "TRAV", "TRBD", "IGKJ".
group.by	Variable in which to group the diversity calculation.
plot	The type of plot to return - heatmap or barplot.
order	Categorical variable to organize the x-axis, either "gene" or "variance"
scale	Converts the individual count of genes to proportion using the total respective repertoire size
exportTable	Returns the data frame used for forming the graph.
palette	Colors to use in visualization - input any hcl.pals.

Value

ggplot bar diagram or heatmap of gene usage

Examples

```
#Making combined contig data
combined <- combineTCR(contig_list,
                       samples = c("P17B", "P17L", "P18B", "P18L",
                                   "P19B","P19L", "P20B", "P20L"))

vizGenes(combined,
         x.axis = "TRBV",
         y.axis = NULL,
         plot = "heatmap")
```

Index

∗ **Data**
contig_list, 31
mini_contig_list, 38
scRep_example, 46
∗ **Loading_and_Processing_Contigs**
addVariable, 4
combineBCR, 27
combineTCR, 30
createHTOContigList, 31
exportClones, 32
loadContigs, 37
subsetClones, 48
∗ **SC_Functions**
alluvialClones, 4
clonalBias, 7
clonalNetwork, 15
clonalOccupy, 17
clonalOverlay, 20
combineExpression, 29
getCirclize, 34
highlightClones, 36
StartracDiversity, 46
∗ **Summarize_Repertoire**
percentAA, 39
percentGenes, 40
percentKmer, 41
percentVJ, 42
positionalEntropy, 43
positionalProperty, 44
∗ **Visualizing_Clones**
clonalAbundance, 6
clonalCluster, 8
clonalCompare, 9
clonalDiversity, 11
clonalHomeostasis, 13
clonalLength, 14
clonalOverlap, 18
clonalProportion, 21
clonalQuant, 22
clonalRarefaction, 23
clonalScatter, 24
clonalSizeDistribution, 26
vizGenes, 48
∗ **datasets**
mini_contig_list, 38
∗ **internal**
expression2List, 33
getHumanIgPseudoGenes, 36
scRepertoire-package, 3

addVariable, 4
alluvialClones, 4

chordDiagram, *35*
clonalAbundance, 6
clonalBias, 7
clonalBias(), *7*
clonalCluster, 8
clonalCompare, 9
clonalDiversity, 11
clonalDiversity(), *43*
clonalHomeostasis, 13
clonalLength, 14
clonalNetwork, 15
clonalOccupy, 17
clonalOverlap, 18
clonalOverlay, 20
clonalProportion, 21
clonalQuant, 22
clonalRarefaction, 23
clonalScatter, 24
clonalSizeDistribution, 26
combineBCR, *10*, 27
combineBCR(), *4*, *6*, *8*, *9*, *11*, *13*, *15*, *18*, *22–26*, *29*, *32*, *33*, *35*, *37–44*, *48*, *49*
combineExpression, *10*, 29
combineExpression(), *4–9*, *11*, *13*, *15–18*, *20*, *22–27*, *29*, *30*, *33*, *34*, *36*, *39–44*, *47*, *49*

combineTCR, *10*, 30
combineTCR(), *4*, *6*, *8*, *9*, *11*, *13*, *15*, *18*, *22–27*, *29*, *32*, *33*, *35*, *37–44*, *48*, *49*
contig_list, 31
contig_list(), *38*
createHTOContigList, 31
createHTOContigList(), *31*

exportClones, 32
expression2List, 33

getCirclize, 34
getContigDoublets, 35
getHumanIgPseudoGenes, 36

hcl.pals, *5–7*, *10*, *12*, *14–17*, *19*, *22–26*, *39–44*, *47*, *49*
highlightClones, 36

igraph::components(), *27*
iNEXT::iNEXT(), *23*

loadContigs, 37
loadContigs(), *28*, *31*

mini_contig_list, 38

percentAA, 39
percentGenes, 40
percentKmer, 41
percentVJ, 42
percentVJ(), *40*
positionalEntropy, 43
positionalProperty, 44

quietBCRgenes *(*quietVDJgenes*)*, 45
quietTCRgenes *(*quietVDJgenes*)*, 45
quietVDJgenes, 45
quietVDJgenes(), *36*

scRep_example, 46
scRepertoire *(*scRepertoire-package*)*, 3
scRepertoire-package, 3
StartracDiversity, 46
subsetClones, 48

vizGenes, 48