

Package ‘CytoGLMM’

June 12, 2025

Type Package

Title Conditional Differential Analysis for Flow and Mass Cytometry Experiments

Version 1.17.0

Description The CytoGLMM R package implements two multiple regression strategies: A bootstrapped generalized linear model (GLM) and a generalized linear mixed model (GLMM). Most current data analysis tools compare expressions across many computationally discovered cell types. CytoGLMM focuses on just one cell type. Our narrower field of application allows us to define a more specific statistical model with easier to control statistical guarantees. As a result, CytoGLMM finds differential proteins in flow and mass cytometry data while reducing biases arising from marker correlations and safeguarding against false discoveries induced by patient heterogeneity.

License LGPL-3

URL <https://christofseiler.github.io/CytoGLMM>,
<https://github.com/ChristofSeiler/CytoGLMM>

BugReports <https://github.com/ChristofSeiler/CytoGLMM/issues>

Encoding UTF-8

LazyData true

Imports stats, methods, BiocParallel, RColorBrewer, cowplot, dplyr,
factoextra, flexmix, ggplot2, magrittr, pheatmap, stringr,
strucchange, tibble, ggrepel, MASS, Matrix, tidyr, caret,
rlang, grDevices

Suggests knitr, rmarkdown, testthat, BiocStyle

VignetteBuilder knitr

RoxygenNote 7.3.1

biocViews FlowCytometry, Proteomics, SingleCell, CellBasedAssays,
CellBiology, ImmunoOncology, Regression, StatisticalMethod,
Software

git_url <https://git.bioconductor.org/packages/CytoGLMM>

git_branch devel

git_last_commit 6e5b75b

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-06-12
Author Christof Seiler [aut, cre] (ORCID:
 <<https://orcid.org/0000-0001-8802-3642>>)
Maintainer Christof Seiler <christof.seiler@maastrichtuniversity.nl>

Contents

cytoflexmix	2
cytoglm	4
cytogroup	5
cytostab	6
cyto_check	7
generate_data	8
is_unpaired	8
plot.cytoflexmix	9
plot.cytoglm	9
plot.cytogroup	10
plot_coeff	11
plot_heatmap	12
plot_lda	13
plot_mds	14
plot_model_selection	15
plot_prcomp	15
print.cytoglm	16
remove_samples	17
summary.cytoglm	17
Index	19

cytoflexmix	<i>Logistic mixture regression</i>
-------------	------------------------------------

Description

Logistic mixture regression

Usage

```
cytoflexmix(  
  df_samples_subset,  
  protein_names,  
  condition,  
  group = "donor",  
  cell_n_min = Inf,  
  cell_n_subsample = 0,  
  ks = seq_len(10),  
  num_cores = 1  
)
```

Arguments

<code>df_samples_subset</code>	Data frame or tibble with proteins counts, cell condition, and group information
<code>protein_names</code>	A vector of column names of protein to use in the analysis
<code>condition</code>	The column name of the condition variable
<code>group</code>	The column name of the group variable
<code>cell_n_min</code>	Remove samples that are below this cell counts threshold
<code>cell_n_subsample</code>	Subsample samples to have this maximum cell count
<code>ks</code>	A vector of cluster sizes
<code>num_cores</code>	Number of computing cores

Value

A list of class `cytoglm` containing

<code>flexmixfits</code>	list of <code>flexmix</code> objects
<code>df_samples_subset</code>	possibly subsampled <code>df_samples_subset</code> table
<code>protein_names</code>	input protein names
<code>condition</code>	input condition variable
<code>group</code>	input group names
<code>cell_n_min</code>	input <code>cell_n_min</code>
<code>cell_n_subsample</code>	input <code>cell_n_subsample</code>
<code>ks</code>	input <code>ks</code>
<code>num_cores</code>	input <code>num_cores</code>

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
mix_fit <- CytoGLMM::cytoflexmix(df,
                                protein_names = protein_names,
                                condition = "condition",
                                group = "donor",
                                ks = 2)

mix_fit
```

cytoglm

*Fit GLM with bootstrap resampling***Description**

Fit GLM with bootstrap resampling

Usage

```
cytoglm(
  df_samples_subset,
  protein_names,
  condition,
  group = "donor",
  covariate_names = NULL,
  cell_n_min = Inf,
  cell_n_subsample = 0,
  num_boot = 100,
  num_cores = 1
)
```

Arguments

<code>df_samples_subset</code>	Data frame or tibble with proteins counts, cell condition, and group information
<code>protein_names</code>	A vector of column names of protein to use in the analysis
<code>condition</code>	The column name of the condition variable
<code>group</code>	The column name of the group variable
<code>covariate_names</code>	The column names of covariates
<code>cell_n_min</code>	Remove samples that are below this cell counts threshold
<code>cell_n_subsample</code>	Subsample samples to have this maximum cell count
<code>num_boot</code>	Number of bootstrap samples
<code>num_cores</code>	Number of computing cores

ValueA list of class `cytoglm` containing

<code>tb_coef</code>	coefficient table
<code>df_samples_subset</code>	possibly subsampled <code>df_samples_subset</code> table
<code>protein_names</code>	input protein names
<code>condition</code>	input condition variable
<code>group</code>	input group names
<code>covariate_names</code>	input covariates

```

cell_n_min      input cell_n_min
cell_n_subsample      input cell_n_subsample

unpaired        true if unpaired samples were provided as input
num_boot        input num_boot
num_cores       input num_cores
formula_str     formula use in the regression model

```

Examples

```

set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
glm_fit <- CytoGLMM::cytoglm(df,
                             protein_names = protein_names,
                             condition = "condition",
                             group = "donor",
                             num_boot = 10) # in practice >=1000

glm_fit

```

cytogroup

Group-specific fixed effects model

Description

Group-specific fixed effects model

Usage

```

cytogroup(
  df_samples_subset,
  protein_names,
  condition,
  group = "donor",
  cell_n_min = Inf,
  cell_n_subsample = 0
)

```

Arguments

```

df_samples_subset      Data frame or tibble with proteins counts, cell condition, and group information
protein_names          A vector of column names of protein to use in the analysis
condition              The column name of the condition variable
group                  The column name of the group variable
cell_n_min             Remove samples that are below this cell counts threshold
cell_n_subsample       Subsample samples to have this maximum cell count

```

Value

A list of class `cytoglm` containing

```
groupfit      glm object
df_samples_subset possibly subsampled df_samples_subset table
protein_names input protein names
condition     input condition variable
group         input group names
cell_n_min    input cell_n_min
cell_n_subsample input cell_n_subsample
```

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
group_fit <- CytoGLMM::cytogroup(df,
                                protein_names = protein_names,
                                condition = "condition",
                                group = "donor")

group_fit
```

cytostab

Evaluate parameter stability with respect to gating scheme

Description

Evaluate parameter stability with respect to gating scheme

Usage

```
cytostab(
  df_samples_subset,
  protein_names,
  condition,
  group = "donor",
  cell_n_min = Inf,
  cell_n_subsample = 0
)
```

Arguments

```
df_samples_subset    Data frame or tibble with proteins counts, cell condition, and group information
protein_names        A vector of column names of protein to use in the analysis
condition             The column name of the condition variable
```

group	The column name of the group variable
cell_n_min	Remove samples that are below this cell counts threshold
cell_n_subsample	Subsample samples to have this maximum cell count

Value

A data frame

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
stab <- CytoGLMM::cytostab(df,
                           protein_names = protein_names,
                           condition = "condition",
                           group = "donor")
stab
```

cyto_check	<i>Check if input to cytoxxx function have errors</i>
------------	---

Description

Check if input to cytoxxx function have errors

Usage

```
cyto_check(cell_n_subsample, cell_n_min, protein_names)
```

Arguments

cell_n_subsample	Subsample samples to have this maximum cell count
cell_n_min	A vector of column names of protein to use in the analysis
protein_names	A vector of column names of protein to use in the analysis

Value

NULL.

generate_data	<i>Generate dataset for vignettes and simulation studies</i>
---------------	--

Description

Generate dataset for vignettes and simulation studies

Usage

```
generate_data()
```

Value

`tibble` data frame

Examples

```
set.seed(23)
df <- generate_data()
str(df)
df
```

is_unpaired	<i>Check if samples match or paired on condition</i>
-------------	--

Description

Check if samples match or paired on condition

Usage

```
is_unpaired(df_samples_subset, condition, group)
```

Arguments

df_samples_subset	Data frame or tibble with proteins counts, cell condition, and group information
condition	The column name of the condition variable
group	The column name of the group variable

Value

A boolean

plot.cytoflexmix	<i>Plot all components of mixture regression</i>
------------------	--

Description

Plot all components of mixture regression

Usage

```
## S3 method for class 'cytoflexmix'
plot(x, k = NULL, separate = FALSE, ...)
```

Arguments

x	A cytoflexmix class
k	Number of clusters
separate	create two separate ggplot2 objects
...	Other parameters

Value

[ggplot2](#) object

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
mix_fit <- CytoGLMM::cytoflexmix(df,
                                protein_names = protein_names,
                                condition = "condition",
                                group = "donor",
                                ks = 2)

plot(mix_fit)
```

plot.cytoglm	<i>Plot bootstrapped coefficients</i>
--------------	---------------------------------------

Description

Plot bootstrapped coefficients

Usage

```
## S3 method for class 'cytoglm'
plot(x, order = FALSE, separate = FALSE, ...)
```

Arguments

x	A cytoglm class
order	Order the markers according to the mangintute of the coefficients
separate	create two separate ggplot2 objects
...	Other parameters

Value

[ggplot2](#) object

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
glm_fit <- CytoGLMM::cytoglm(df,
                             protein_names = protein_names,
                             condition = "condition",
                             group = "donor",
                             num_boot = 10) # in practice >=1000
plot(glm_fit)
```

plot.cytogroup

Plot fixded coefficients of group-specific fixed effects model

Description

Plot fixded coefficients of group-specific fixed effects model

Usage

```
## S3 method for class 'cytgroup'
plot(x, order = FALSE, separate = FALSE, ...)
```

Arguments

x	A cytoglmm class
order	Order the markers according to the mangintute of the coefficients
separate	create two separate ggplot2 objects
...	Other parameters

Value

[ggplot2](#) object

Examples

```

set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
group_fit <- CytoGLMM::cytogroup(df,
                                protein_names = protein_names,
                                condition = "condition",
                                group = "donor")

plot(group_fit)

```

plot_coeff

*Helper function to plot regression coefficient***Description**

Helper function to plot regression coefficient

Usage

```

plot_coeff(
  tb,
  title_str,
  title_str_right,
  xlab_str,
  redline = 0,
  order = FALSE,
  separate = FALSE
)

```

Arguments

tb	A data frame
title_str	Title string for summary plot
title_str_right	Title for bootstrap sample plot
xlab_str	Label on x-axis
redline	Point on x-axis to draw the red line
order	Order the markers according to the magnitude of the coefficients
separate	Plot both summary and bootstrap samples

Value

[ggplot2](#) object or list of two objects if separate is true

plot_heatmap

*Heatmap of median marker expression***Description**

Heatmap of median marker expression

Usage

```
plot_heatmap(
  df_samples,
  sample_info_names,
  protein_names,
  arrange_by_1,
  arrange_by_2 = "",
  cluster_cols = FALSE,
  fun = median
)
```

Arguments

df_samples	Data frame or tibble with proteins counts, cell condition, and group information
sample_info_names	Column names that contain information about the cell, e.g. donor, condition, file name, or cell type
protein_names	A vector of column names of protein to use in the analysis
arrange_by_1	Column name
arrange_by_2	Column name
cluster_cols	Apply hierarchical cluster to columns
fun	Summary statistics of marker expression

Value

pheatmap object

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
CytoGLMM::plot_heatmap(df,
  protein_names = protein_names,
  sample_info_names = c("donor", "condition"),
  arrange_by_1 = "condition")
```

plot_lda	<i>LDA on marker expression</i>
----------	---------------------------------

Description

LDA on marker expression

Usage

```
plot_lda(  
  df_samples,  
  protein_names,  
  group,  
  cor_scaling_factor = 1,  
  arrow_color = "black",  
  marker_color = "black",  
  marker_size = 5  
)
```

Arguments

df_samples	Data frame or tibble with proteins counts, cell condition, and group information
protein_names	A vector of column names of protein to use in the analysis
group	The column name of the group variable
cor_scaling_factor	Scaling factor of circle of correlations
arrow_color	Color of correlation circle
marker_color	Colors of marker names
marker_size	Size of markerr names

Value

[ggplot2](#) object

Examples

```
set.seed(23)  
df <- generate_data()  
protein_names <- names(df)[3:12]  
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))  
df$condition <- rep(c("A", "B", "C", "D"), each = length(df$condition)/4)  
CytoGLMM::plot_lda(df,  
  protein_names = protein_names,  
  group = "condition",  
  cor_scaling_factor = 2)
```

plot_mds	<i>MDS on median marker expression</i>
----------	--

Description

MDS on median marker expression

Usage

```
plot_mds(
  df_samples,
  protein_names,
  sample_info_names,
  color,
  sample_label = ""
)
```

Arguments

df_samples	Data frame or tibble with proteins counts, cell condition, and group information
protein_names	A vector of column names of protein to use in the analysis
sample_info_names	Column names that contain information about the cell, e.g. donor, condition, file name, or cell type
color	Column name
sample_label	Column name

Value

[cowplot](#) object

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
CytoGLMM::plot_mds(df,
  protein_names = protein_names,
  sample_info_names = c("donor", "condition"),
  color = "condition")
```

plot_model_selection *Plot model selection to choose number optimal number of clusters*

Description

Plot model selection to choose number optimal number of clusters

Usage

```
plot_model_selection(fit, k = NULL)
```

Arguments

fit	A cytoflexmix class
k	Number of clusters

Value

cowplot object

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
mix_fit <- CytoGLMM::cytoflexmix(df,
                                protein_names = protein_names,
                                condition = "condition",
                                group = "donor",
                                ks = 1:2)

plot_model_selection(mix_fit)
```

plot_prcomp *Plot PCA of subsampled data using ggplot*

Description

Plot PCA of subsampled data using ggplot

Usage

```
plot_prcomp(
  df_samples,
  protein_names,
  color_var = "treatment",
  subsample_size = 10000,
  repel = TRUE
)
```

Arguments

df_samples	Data frame or tibble with proteins counts, cell condition, and group information
protein_names	A vector of column names of protein to use in the analysis
color_var	A column name
subsample_size	Subsample per color_var variable
repel	Repel labels

Value

cowplot object

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
CytoGLMM::plot_prcomp(df,
  protein_names = protein_names,
  color_var = "condition")
```

print.cytoglm

Extact and print bootstrap GLM fit

Description

Extact and print bootstrap GLM fit

Usage

```
## S3 method for class 'cytoglm'
print(x, ...)
```

Arguments

x	A cytoglm class
...	Other parameters

Value

NULL.

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
glm_fit <- CytoGLMM::cytoglm(df,
  protein_names = protein_names,
  condition = "condition",
```

```

                                group = "donor",
                                num_boot = 10) # in practice >=1000
print(glm_fit)

```

remove_samples	<i>Remove samples based on low cell counts</i>
----------------	--

Description

Remove samples based on low cell counts

Usage

```
remove_samples(df_samples_subset, condition, group, unpaired, cell_n_min)
```

Arguments

df_samples_subset	Data frame or tibble with proteins counts, cell condition, and group information
condition	The column name of the condition variable
group	The column name of the group variable
unpaired	true if unpaired samples were provided as input
cell_n_min	Remove samples that are below this cell counts threshold

Value

NULL.

summary.cytoglm	<i>Extact and calculate p-values of bootstrap GLM fit</i>
-----------------	---

Description

Extact and calculate p-values of bootstrap GLM fit

Usage

```
## S3 method for class 'cytoglm'
summary(object, method = "BH", ...)
```

Arguments

object	A cytoglm class
method	Multiple comparison adjustment method
...	Other parameters

Value

[tibble](#) data frame

Examples

```
set.seed(23)
df <- generate_data()
protein_names <- names(df)[3:12]
df <- dplyr::mutate_at(df, protein_names, function(x) asinh(x/5))
glm_fit <- CytoGLMM::cytoglm(df,
                             protein_names = protein_names,
                             condition = "condition",
                             group = "donor",
                             num_boot = 10) # in practice >=1000
summary(glm_fit)
```

Index

cowplot, [14–16](#)
cyto_check, [7](#)
cytoflexmix, [2](#)
cytoglm, [4](#)
cytogroup, [5](#)
cytostab, [6](#)

flexmix, [3](#)

generate_data, [8](#)
ggplot2, [9–11](#), [13](#)
glm, [6](#)

is_unpaired, [8](#)

pheatmap, [12](#)
plot.cytoflexmix, [9](#)
plot.cytoglm, [9](#)
plot.cytogroup, [10](#)
plot_coeff, [11](#)
plot_heatmap, [12](#)
plot_lda, [13](#)
plot_mds, [14](#)
plot_model_selection, [15](#)
plot_prcomp, [15](#)
print.cytoglm, [16](#)

remove_samples, [17](#)

summary.cytoglm, [17](#)

tibble, [8](#), [17](#)