

Package ‘LIPIDIFy’

October 29, 2026

Type Package

Title Comprehensive Lipidomics Data Analysis with Interactive Visualization

Version 0.99.7

Description Provides a comprehensive toolkit for end-to-end lipidomics data analysis, including missing value imputation, batch effect correction, normalization, differential abundance analysis using limma and edgeR, gene set enrichment analysis, and extensive visualization capabilities. Lipid names are automatically classified by class, subclass, and fatty-acid saturation. Features both an interactive Shiny interface for bench biologists and fully scriptable R functions for bioinformaticians. Supports flexible custom lipid classification schemes and user-defined enrichment sets.

License MIT + file LICENSE

Encoding UTF-8

LazyData false

Depends R (>= 4.5.0)

Imports shiny (>= 1.8.0), shinydashboard, ggplot2 (>= 3.5.0), ggrepel, plotly, DT, tidyr, dplyr, scales, gridExtra, grid, pheatmap, limma, edgeR, fgsea, FactoMineR, pls, openxlsx, rmarkdown, stringr, withr, utils, stats, grDevices

Suggests BiocStyle, knitr, testthat (>= 3.0.0), impute, sva, vsn, SummarizedExperiment, tinytex, shinytest2, chromote

VignetteBuilder knitr

biocViews Software, Lipidomics, MassSpectrometry, Normalization, Preprocessing, DifferentialExpression, GeneSetEnrichment, Visualization, ShinyApps, MultipleComparison, BatchEffect, QualityControl, DataImport, Classification

URL <https://github.com/fayrouzhammal/LIPIDIFy>

BugReports <https://github.com/fayrouzhammal/LIPIDIFy/issues>

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

git_url <https://git.bioconductor.org/packages/LIPIDIFy>

git_branch devel

git_last_commit 69e5b67

git_last_commit_date 2026-09-23

Repository Bioconductor 3.24

Date/Publication 2026-10-28

Author Fayrouz Hammal [aut, cre] (ORCID:

<<https://orcid.org/0000-0002-7612-4953>>),

Karen Sheppard [fnd] (NHMRC of Australia grant #2020050)

Maintainer Fayrouz Hammal <fayrouz.hammal@petermac.org>

Contents

LIPIDIFY-package	3
apply_normalizations	3
classify_lipids	4
correct_batch_effects	5
create_default_contrasts	6
create_enrichment_barplot	6
create_enrichment_dotplot	7
create_heatmap_robust	8
create_lipid_expression_barplot	8
create_pca_plot_with_ellipses	9
create_pipeline_plot	10
create_plsda_plot_with_ellipses	11
create_volcano_plot_labeled	12
determine_saturation	13
export_classification	14
fix_sample_alignment	14
generate_example_data	15
get_imputation_descriptions	15
get_imputation_methods	16
get_normalization_descriptions	16
get_normalization_methods	17
impute_missing_values	17
launch_lipidomics_app	18
load_custom_classification	18
load_custom_enrichment_sets	19
load_lipidomics_data	20
load_lipidomics_data_from_df	20
normalize_log2median	21
normalize_mean	22
normalize_median	22
normalize_pqn	23
normalize_quantile	23
normalize_tic	24
normalize_vsn	24
perform_differential_analysis	25
perform_enrichment_analysis	26
perform_pca	27
perform_plsda	28
test_saturation_classification	29
visualize_raw_data	29
visualize_raw_data_improved	30

Index**31**

LIPIDIFY-package	<i>LIPIDIFY: Comprehensive Lipidomics Data Analysis with Interactive Visualization</i>
------------------	--

Description

LIPIDIFY provides a comprehensive toolkit for end-to-end lipidomics data analysis, including missing value imputation, batch effect correction, normalization, differential abundance analysis using limma and edgeR, gene set enrichment analysis, and extensive visualization capabilities. Lipid names are automatically classified by class, subclass, and fatty-acid saturation. The package offers both an interactive Shiny interface for bench biologists (see [launch_lipidomics_app](#)) and fully scriptable R functions for bioinformaticians. It supports flexible custom lipid classification schemes and user-defined enrichment sets.

Getting started

See `vignette("LIPIDIFY")` for a full walkthrough of the programmatic workflow.

Author(s)

Maintainer: Fayrouz Hammal <fayrouz.hammal@petermac.org> ([ORCID](#))

Authors:

- Fayrouz Hammal <fayrouz.hammal@petermac.org> ([ORCID](#))

Other contributors:

- Karen Sheppard (NHMRC of Australia grant #2020050) [funder]

See Also

Useful links:

- <https://github.com/fayrouzhammal/LIPIDIFY>
- Report bugs at <https://github.com/fayrouzhammal/LIPIDIFY/issues>

<code>apply_normalizations</code>	<i>Apply a Sequence of Normalization Methods</i>
-----------------------------------	--

Description

Applies normalization methods in the order supplied, passing the output of each step as the input to the next.

Usage

```
apply_normalizations(data, methods)
```

Arguments

data	Numeric matrix with samples in rows and lipids in columns.
methods	Character vector of method names as returned by <code>get_normalization_methods()</code> .

Details

Method names are matched exactly against `get_normalization_methods()`; an unrecognised name leaves the data unchanged. "VSN" and "Log2Median" are separate methods – "VSN" calls [normalize_vsn](#) (Bioconductor [vsn](#)) and "Log2Median" calls [normalize_log2median](#). If [vsn](#) is not installed, "VSN" raises an error; it never falls back to another method.

Value

Normalized numeric matrix of the same dimensions as data.

See Also

[normalize_vsn](#), [normalize_log2median](#).

Examples

```
m <- matrix(rlnorm(60, 8, 1), nrow = 6, ncol = 10)
apply_normalizations(m, c("TIC", "Log2"))
```

classify_lipids	<i>Classify Lipids Based on Their Names</i>
-----------------	---

Description

Classifies a vector of lipid names into lipid group, type, and saturation category using regular-expression pattern matching.

Usage

```
classify_lipids(lipid_names)
```

Arguments

lipid_names	Character vector of lipid names.
-------------	----------------------------------

Value

Data frame with columns Lipid, LipidGroup, LipidType, and Saturation.

Examples

```
classify_lipids(c("PC 16:0_18:1", "TG 16:0_18:1_20:4", "Cer 16:0"))
```

correct_batch_effects *Correct Batch Effects from a Normalised Lipidomics Matrix*

Description

Removes known technical batch effects while preserving biological signal. Batch correction should be applied **after** normalisation.

Usage

```
correct_batch_effects(
  data_matrix,
  metadata,
  batch_column,
  group_column = "Sample Group",
  method = "limma"
)
```

Arguments

data_matrix	Numeric matrix with samples as rows and lipids as columns (typically the output of apply_normalizations).
metadata	Data frame of sample metadata aligned with data_matrix (same row order).
batch_column	Character. Name of the column in metadata containing batch labels.
group_column	Character. Name of the biological group column to protect from removal (default "Sample Group"). Pass NULL to skip group protection.
method	One of "limma" (default) or "combat".

Details

Two methods are supported:

"limma" Uses [removeBatchEffect](#). Requires only the limma package (already a dependency). Suitable for most experimental designs.

"combat" Uses `sva::ComBat` with parametric empirical Bayes adjustment. Requires the **sva** Bioconductor package (`BiocManager::install("sva")`). Generally more robust when batch effects are large.

Value

Batch-corrected numeric matrix of the same dimensions as data_matrix.

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
d$metadata$Batch <- rep(c("Batch1", "Batch2"), each = 10)
corrected <- correct_batch_effects(norm, d$metadata,
  batch_column = "Batch"
)
dim(corrected)
```

`create_default_contrasts`*Create Default Contrasts*

Description

Creates default pairwise contrasts from group levels. If the levels contain special characters that are invalid for limma/edgeR, they should already be sanitized before calling this function.

Usage

```
create_default_contrasts(group_levels)
```

Arguments

`group_levels` Character vector of group level names (e.g., `c("Control", "Treatment", "Resistant")`)

Value

Character vector of limma-style contrast strings (e.g., "Treatment - Control")

Examples

```
create_default_contrasts(c("A", "B", "C"))
```

`create_enrichment_barplot`*Create an Enrichment Barplot*

Description

Create an Enrichment Barplot

Usage

```
create_enrichment_barplot(  
  enrichment_data,  
  title = "Enrichment Analysis",  
  max_pathways = 15  
)
```

Arguments

`enrichment_data` Data frame of fgsea results.

`title` Plot title.

`max_pathways` Maximum number of pathways (top by p-value).

Value

A ggplot2 object.

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
cls <- classify_lipids(colnames(norm))
res <- perform_differential_analysis(norm, d$metadata, "Sample Group",
  contrasts_list = NULL, method = "limma"
)
enrich <- perform_enrichment_analysis(res$results, cls, min_set_size = 3)
p <- create_enrichment_barplot(enrich[[1]][["LipidGroup"]])
print(p)
```

create_enrichment_dotplot

Create an Enrichment Dotplot

Description

Create an Enrichment Dotplot

Usage

```
create_enrichment_dotplot(
  enrichment_data,
  title = "Enrichment Analysis",
  max_pathways = 15
)
```

Arguments

enrichment_data	Data frame of fgsea results.
title	Plot title.
max_pathways	Maximum number of pathways (top by p-value).

Value

A ggplot2 object.

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
cls <- classify_lipids(colnames(norm))
res <- perform_differential_analysis(norm, d$metadata, "Sample Group",
  contrasts_list = NULL, method = "limma"
)
enrich <- perform_enrichment_analysis(res$results, cls, min_set_size = 3)
p <- create_enrichment_dotplot(enrich[[1]][["LipidGroup"]])
print(p)
```

`create_heatmap_robust` *Create a Robust Heatmap of Top Variable Features*

Description

Create a Robust Heatmap of Top Variable Features

Usage

```
create_heatmap_robust(
  data_matrix,
  metadata,
  group_column = "Sample Group",
  top_n = 50,
  classification_data = NULL,
  title = "Heatmap"
)
```

Arguments

<code>data_matrix</code>	Numeric matrix (features as rows, samples as columns).
<code>metadata</code>	Metadata data frame (samples as rows).
<code>group_column</code>	Name of the group column in metadata.
<code>top_n</code>	Maximum number of features to display.
<code>classification_data</code>	Optional classification data frame for row annotation (must have a Lipid column).
<code>title</code>	Heatmap title.

Value

A pheatmap object, or a ggplot2 error plot.

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
create_heatmap_robust(t(norm), d$metadata, "Sample Group", top_n = 10)
```

`create_lipid_expression_barplot`
Create a Lipid Expression Barplot Ordered by Group

Description

Produces per-lipid barplots coloured by sample group. Samples are automatically sorted by group (then alphabetically within group) for a cleaner visual.

Usage

```
create_lipid_expression_barplot(
  data_matrix,
  metadata,
  selected_lipids,
  selected_samples = NULL,
  selected_groups = NULL,
  group_column = "Sample Group",
  data_type = "normalized"
)
```

Arguments

<code>data_matrix</code>	Numeric matrix (samples as rows, lipids as columns).
<code>metadata</code>	Metadata data frame.
<code>selected_lipids</code>	Character vector of lipid names to plot.
<code>selected_samples</code>	Optional character vector of sample names to retain.
<code>selected_groups</code>	Optional character vector of group names to retain.
<code>group_column</code>	Name of the group column in metadata.
<code>data_type</code>	Label for the y-axis subtitle ("raw" or "normalized").

Value

A single ggplot2 object (one lipid) or a named list of ggplot2 objects (multiple lipids).

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
p <- create_lipid_expression_barplot(
  d$numeric_data, d$metadata,
  selected_lipids = colnames(d$numeric_data)[1],
  group_column = "Sample Group"
)
print(p)
```

create_pca_plot_with_ellipses

Create a PCA Plot with Optional Confidence or Visual Ellipses

Description

The colour/fill legends are merged so that ellipses do not introduce duplicate legend keys. Sample labels are kept separate from group labels.

Usage

```
create_pca_plot_with_ellipses(
  pca_data,
  variance_explained,
  ellipse_type = "none",
  confidence_level = 0.95,
  title = "PCA Analysis",
  show_sample_labels = FALSE
)
```

Arguments

pca_data	Data frame with columns PC1, PC2, Group and (optionally) Sample for point labels.
variance_explained	Numeric vector of length ≥ 2 with the percent variance explained by PC1 and PC2.
ellipse_type	One of "none", "confidence", or "visual".
confidence_level	Numeric confidence level for "confidence" ellipses (default 0.95).
title	Plot title.
show_sample_labels	Logical. If TRUE, sample names are shown as text labels next to each point.

Value

A ggplot2 object.

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
pca_res <- perform_pca(norm, d$metadata, "Sample Group")
p <- create_pca_plot_with_ellipses(pca_res$pca_data, pca_res$variance_explained)
print(p)
```

create_pipeline_plot *Quick QC Plot for a Normalized Data Matrix*

Description

Quick QC Plot for a Normalized Data Matrix

Usage

```
create_pipeline_plot(
  data_matrix,
  title = "Normalization Pipeline",
  metadata = NULL,
  group_column = "Sample Group",
  plot_type = "boxplot",
```

```

    view_mode = "sample",
    top_n = NULL
  )

```

Arguments

<code>data_matrix</code>	Numeric matrix or data frame (samples as rows, lipids as columns).
<code>title</code>	Plot title string.
<code>metadata</code>	Optional metadata data frame (same row order) for group colouring.
<code>group_column</code>	Name of the group column in metadata.
<code>plot_type</code>	One of "boxplot", "violin", or "density". Defaults to "boxplot".
<code>view_mode</code>	Either "sample" (one box/violin per sample; the default, preserving previous behaviour) or "lipid" (one box/violin per lipid). Ignored for "density", which always shows the intensity distribution.
<code>top_n</code>	Integer or NULL. In "sample" view, restrict the plot to the top_n most variable samples (NULL, the default, shows all). In "lipid" view, restrict to the top_n most variable lipids (NULL defaults to 30).

Value

A ggplot2 object.

Examples

```

m <- matrix(rlnorm(60, 8, 1), nrow = 6, ncol = 10)
p <- create_pipeline_plot(m, title = "Test Pipeline")
print(p)

```

```
create_plsda_plot_with_ellipses
```

Create a PLS-DA Plot with Optional Ellipses

Description

Create a PLS-DA Plot with Optional Ellipses

Usage

```

create_plsda_plot_with_ellipses(
  plsda_data,
  ellipse_type = "none",
  confidence_level = 0.95,
  title = "PLS-DA Analysis",
  show_sample_labels = FALSE
)

```

Arguments

plsda_data	Data frame with columns Comp1, Comp2, Group, and (optionally) Sample.
ellipse_type	One of "none", "confidence", or "visual".
confidence_level	Numeric confidence level (default 0.95).
title	Plot title.
show_sample_labels	Logical. Show sample name labels if TRUE.

Value

A ggplot2 object.

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
res <- perform_plsda(norm, d$metadata, "Sample Group")
p <- create_plsda_plot_with_ellipses(res$scores_data)
print(p)
```

create_volcano_plot_labeled

Create a Volcano Plot with Optional Classification Colouring

Description

Significant lipids ($\text{adj.P.Val} < \text{pval_threshold}$ AND $|\log\text{FC}| > \log\text{fc_threshold}$) are coloured; non-significant points are grey. When `classification_data` is supplied, significant lipids are coloured by the selected classification column.

Usage

```
create_volcano_plot_labeled(
  results,
  title = "Volcano Plot",
  logfc_threshold = 1,
  pval_threshold = 0.05,
  top_labels = 15,
  classification_data = NULL,
  color_by = NULL
)
```

Arguments

results	Data frame of differential analysis results (must have columns logFC and adj.P.Val; row names = lipid names).
title	Plot title.
logfc_threshold	Absolute log-fold-change threshold.

pval_threshold Adjusted p-value threshold.
 top_labels Number of top significant lipids to label.
 classification_data
 Optional classification data frame with a Lipid column.
 color_by Column in classification_data to use for colouring.

Value

A ggplot2 object.

Examples

```

d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
res <- perform_differential_analysis(norm, d$metadata, "Sample Group",
  contrasts_list = NULL, method = "limma"
)
p <- create_volcano_plot_labeled(res$results[[1]])
print(p)

```

determine_saturation *Determine Fatty-Acid Saturation from a Lipid Name*

Description

Parses standard lipid name notation to count double bonds and classifies the species as SFA (0 double bonds), MUFA (1) or PUFA (>1).

Usage

```
determine_saturation(lipid_name)
```

Arguments

lipid_name A single character string with the lipid name.

Value

One of "SFA", "MUFA", "PUFA", or "Unclassified".

Examples

```

determine_saturation("PC 16:0_18:1") # "MUFA"
determine_saturation("PE 18:0_18:0") # "SFA"
determine_saturation("TG 16:0_18:1_20:4") # "PUFA"

```

`export_classification` *Export Lipid Classification to CSV*

Description

Export Lipid Classification to CSV

Usage

```
export_classification(classification, file_path)
```

Arguments

`classification` Data frame with lipid classifications.
`file_path` Output file path.

Value

Invisibly returns TRUE on success.

Examples

```
cls <- classify_lipids(c("PC 16:0_18:1", "PE 18:0_20:4"))
tmp <- tempfile(fileext = ".csv")
export_classification(cls, tmp)
unlink(tmp)
```

`fix_sample_alignment` *Align Samples Between Data Matrix and Metadata*

Description

Align Samples Between Data Matrix and Metadata

Usage

```
fix_sample_alignment(data_matrix, metadata)
```

Arguments

`data_matrix` Numeric matrix (features as rows, samples as columns).
`metadata` Metadata data frame.

Value

Named list with aligned `data_matrix` and `metadata`.

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
aligned <- fix_sample_alignment(t(d$numeric_data), d$metadata)
names(aligned)
```

`generate_example_data` *Generate Example Dataset*

Description

Creates a synthetic lipidomics dataset with realistic lipid names and group differences suitable for demonstrating differential analysis capabilities.

Usage

```
generate_example_data()
```

Value

Data frame with simulated lipidomics data including 4 groups with 5 replicates each

Examples

```
example_data <- generate_example_data()
head(example_data[, 1:10])
```

`get_imputation_descriptions`*Return Human-Readable Descriptions of Imputation Methods*

Description

Return Human-Readable Descriptions of Imputation Methods

Usage

```
get_imputation_descriptions()
```

Value

Named character vector (name = method key, value = description).

Examples

```
descs <- get_imputation_descriptions()
cat(descs["half_min"])
```

`get_imputation_methods`*Return Available Imputation Method Names*

Description

Return Available Imputation Method Names

Usage

```
get_imputation_methods()
```

Value

Character vector of imputation method names supported by `impute_missing_values`.

Examples

```
get_imputation_methods()
```

`get_normalization_descriptions`*Return Human-Readable Descriptions of Normalization Methods*

Description

Used by the Shiny app to populate help text.

Usage

```
get_normalization_descriptions()
```

Value

Named character vector (name = method key, value = description).

Examples

```
descs <- get_normalization_descriptions()
cat(descs["TIC"])
```

get_normalization_methods

Return Available Normalization Method Names

Description

"Log2Median" and "VSN" are two distinct methods: "Log2Median" applies a fixed $\log_2(x + 1)$ transform plus median centering, while "VSN" performs genuine variance-stabilising calibration via `vsn::justvsn()` (requires the Bioconductor **vsn** package).

Usage

```
get_normalization_methods()
```

Value

Character vector of normalization method names supported by `apply_normalizations`.

See Also

[normalize_log2median](#), [normalize_vsn](#).

Examples

```
get_normalization_methods()
```

impute_missing_values *Impute Missing Values in a Lipidomics Data Matrix*

Description

Replaces NA values using the chosen strategy. Imputation should be applied **before** normalisation so that missing values do not bias per-sample scaling factors.

Usage

```
impute_missing_values(data_matrix, method = "half_min", k = 5L, seed = NULL)
```

Arguments

<code>data_matrix</code>	Numeric matrix with samples as rows and lipids as columns.
<code>method</code>	Imputation method. One of "half_min" (default), "min", "zero", "mean", "median", "knn". See get_imputation_descriptions for details.
<code>k</code>	Integer. Number of nearest neighbours for "knn" (ignored for other methods). Default 5.
<code>seed</code>	Optional integer seed for reproducible results. Only consulted when <code>method = "knn"</code> . When <code>NULL</code> (the default) no seed is set and the caller's random-number state is left untouched; supply an integer to run the imputation under <code>withr::with_seed()</code> . Either way the caller's RNG stream is restored on exit. Note that KNN imputation is reproducible regardless of this argument, because <code>impute::impute.knn()</code> seeds its own generator internally via its <code>rng.seed</code> argument; seed controls only the RNG context this call runs in, and does not alter the imputed values.

Value

Imputed numeric matrix of the same dimensions as `data_matrix`.

Examples

```
m <- matrix(c(1000, NA, 3000, NA, 500, 1500), nrow = 2)
impute_missing_values(m, method = "half_min")
```

`launch_lipidomics_app` *Launch the LIPIDIFY Shiny Application*

Description

Starts an interactive Shiny dashboard for end-to-end lipidomics analysis, including data upload, lipid classification, normalization, differential analysis, enrichment analysis, and report generation.

Usage

```
launch_lipidomics_app(port = NULL)
```

Arguments

`port` Integer. Port number for the Shiny server. `NULL` lets Shiny pick a free port automatically.

Value

Launches the Shiny application (does not return a value).

Examples

```
if (interactive()) {
  launch_lipidomics_app()
}
```

`load_custom_classification`
Load Custom Lipid Classification from a CSV File

Description

Load Custom Lipid Classification from a CSV File

Usage

```
load_custom_classification(file_path)
```

Arguments

`file_path` Path to a CSV file with a Lipid column followed by one or more classification columns.

Value

Data frame with Lipid as the first column.

Examples

```
tmp <- tempfile(fileext = ".csv")
write.csv(
  data.frame(
    Lipid = c("PC 16:0_18:1", "PE 18:0"),
    Class = c("Phospholipid", "Phospholipid")
  ),
  tmp,
  row.names = FALSE
)
cls <- load_custom_classification(tmp)
unlink(tmp)
```

load_custom_enrichment_sets

Load Custom Enrichment Sets from a CSV File

Description

The CSV must have columns Lipid and Set_Name. A lipid may appear in multiple rows to belong to multiple sets.

Usage

```
load_custom_enrichment_sets(file_path)
```

Arguments

file_path Path to the CSV file.

Value

Named list of character vectors (one vector per set).

Examples

```
tmp <- tempfile(fileext = ".csv")
write.csv(
  data.frame(
    Lipid = c("PC 16:0_18:1", "PE 18:0"),
    Set_Name = c("Phospholipids", "Phospholipids")
  ),
  tmp,
  row.names = FALSE
)
sets <- load_custom_enrichment_sets(tmp)
unlink(tmp)
```

load_lipidomics_data *Load Lipidomics Data*

Description

Reads a CSV file and separates metadata columns from numeric lipid abundance columns.

Usage

```
load_lipidomics_data(
  file_path,
  metadata_columns = c("Sample Name", "Sample Group", "Tumour ID", "Weight (mg)")
)
```

Arguments

`file_path` Path to the lipidomics data file (CSV format).
`metadata_columns` Character vector of expected metadata column names.

Value

A named list with components: `data` (original data frame), `metadata` (metadata data frame), `numeric_data` (numeric matrix).

Examples

```
# Write a minimal CSV then load it
tmp <- tempfile(fileext = ".csv")
write.csv(
  data.frame(
    "Sample Name" = c("S1", "S2"), "Sample Group" = c("A", "B"),
    "PC 16:0" = c(1000, 2000), check.names = FALSE
  ),
  tmp,
  row.names = FALSE
)
loaded <- load_lipidomics_data(tmp)
dim(loaded$numeric_data)
unlink(tmp)
```

load_lipidomics_data_from_df *Load Lipidomics Data from Data Frame*

Description

Processes a lipidomics data frame by separating metadata and numeric data columns.

Usage

```
load_lipidomics_data_from_df(  
  data_df,  
  metadata_columns = c("Sample Name", "Sample Group", "Tumour ID", "Weight (mg)")  
)
```

Arguments

data_df	Data frame with lipidomics data
metadata_columns	Vector of metadata column names

Value

List containing data components (data, metadata, numeric_data)

Examples

```
data_df <- generate_example_data()  
loaded_data <- load_lipidomics_data_from_df(data_df)  
names(loaded_data)
```

normalize_log2median	<i>Log2 Median Centering Normalization</i>
----------------------	--

Description

Log2-transforms the data ($\log_2(x + 1)$), then median-centres each sample relative to the global median. This is a simplified variance-stabilising step suitable for mass-spectrometry lipidomics data.

Usage

```
normalize_log2median(data)
```

Arguments

data	Numeric matrix (samples as rows, lipids as columns).
------	--

Details

This method is **not** equivalent to the VSN procedure of Huber et al. (2002), which estimates its transformation by maximum likelihood. Log2 Median Centering applies a fixed $\log_2(x + 1)$ transform and a per-sample median shift, and back-transforms to the original scale. For genuine variance-stabilising calibration use the separate [normalize_vsn](#) function (method name "VSN"), which calls `vsns::justvsns()`.

Value

Log2-median-centred numeric matrix.

See Also

[normalize_vsn](#) for true VSN.

Examples

```
m <- matrix(c(1000, 2000, 3000, 4000, 500, 1500), nrow = 2)
normalize_log2median(m)
```

normalize_mean	<i>Mean Normalization</i>
----------------	---------------------------

Description

Scales each sample so its mean equals the global mean across all samples.

Usage

```
normalize_mean(data)
```

Arguments

data Numeric matrix (samples as rows, lipids as columns).

Value

Mean-normalized matrix.

Examples

```
m <- matrix(c(1000, 2000, 3000, 4000, 500, 1500), nrow = 2)
normalize_mean(m)
```

normalize_median	<i>Median Normalization</i>
------------------	-----------------------------

Description

Scales each sample so its median equals the global median across all samples.

Usage

```
normalize_median(data)
```

Arguments

data Numeric matrix (samples as rows, lipids as columns).

Value

Median-normalized matrix.

Examples

```
m <- matrix(c(1000, 2000, 3000, 4000, 500, 1500), nrow = 2)
normalize_median(m)
```

normalize_pqn*PQN Normalization*

Description

Probabilistic Quotient Normalization. Uses the per-feature median across samples as the reference spectrum.

Usage

```
normalize_pqn(data)
```

Arguments

data Numeric matrix (samples as rows, lipids as columns).

Value

PQN-normalized matrix.

Examples

```
m <- matrix(c(1000, 2000, 3000, 4000, 500, 1500), nrow = 2)
normalize_pqn(m)
```

normalize_quantile*Quantile Normalization*

Description

Forces all samples to share an identical intensity distribution. After this step per-sample boxplots will look nearly identical – that is the intended and correct behaviour of quantile normalization.

Usage

```
normalize_quantile(data)
```

Arguments

data Numeric matrix (samples as rows, lipids as columns).

Value

Quantile-normalized matrix of the same dimensions.

Examples

```
m <- matrix(c(1000, 2000, 3000, 4000, 500, 1500), nrow = 2)
normalize_quantile(m)
```

normalize_tic	<i>TIC Normalization</i>
---------------	--------------------------

Description

Divides each sample by its total ion current (row sum) and rescales to the global mean TIC.

Usage

```
normalize_tic(data)
```

Arguments

data	Numeric matrix (samples as rows, lipids as columns).
------	--

Value

TIC-normalized matrix of the same dimensions.

Examples

```
m <- matrix(c(1000, 2000, 3000, 4000, 500, 1500), nrow = 2)
normalize_tic(m)
```

normalize_vsn	<i>VSN (Variance Stabilizing Normalization)</i>
---------------	---

Description

Applies genuine variance-stabilising normalization using `vsn::justvsn()` from the Bioconductor **vsn** package (Huber et al. 2002). The method fits an arcsinh-based (generalised log) transformation whose parameters are estimated by robust maximum likelihood, simultaneously calibrating between-sample differences and stabilising the variance-versus-mean dependence typical of raw intensity data.

Usage

```
normalize_vsn(data, ...)
```

Arguments

data	Numeric matrix or data frame (samples as rows, lipids as columns).
...	Further arguments passed to <code>vsn::justvsn()</code> , e.g. <code>minDataPointsPerStratum</code> .

Details

This is a **different** method from [normalize_log2median](#): VSN estimates its transformation from the data, whereas Log2 Median Centering applies a fixed $\log_2(x + 1)$ transform followed by median centering. VSN is not simply another name for a log transformation, and it is not universally the best choice for every lipidomics dataset – compare pipelines before committing to one.

Orientation. The LIPIDIFY normalization contract is samples as rows and lipids as columns, while `vsn::justvsn()` expects features as rows and samples as columns. This function transposes explicitly before and after the call, and restores the original dimension names; the returned matrix has the same orientation, dimensions and dimnames as data.

Restrictions. Input must be numeric, finite (no Inf/ -Inf), and contain at least 2 samples and at least `minDataPointsPerStratum` (42 by default) lipid features. Samples or features consisting entirely of missing values are rejected, as are samples with fewer than two observed values. NA values are permitted: vsn fits on the observed values and returns NA in the same positions – they are not imputed. Negative values produce a warning because VSN is intended for positive, intensity-like data with a mean-dependent variance; nothing is silently replaced or coerced.

Output is on a generalised-log (roughly $\log_2$) scale, so VSN should not be chained with an additional "Log2" step.

Value

VSN-calibrated numeric matrix with the same dimensions, orientation and dimnames as data.

References

Huber W, von Heydebreck A, Sueltmann H, Poustka A, Vingron M (2002). Variance stabilization applied to microarray data calibration and to the quantification of differential expression. *Bioinformatics* **18**, S96–S104.

See Also

[normalize_log2median](#) for the (separate) $\log_2$ median centering method, and [apply_normalizations](#).

Examples

```
if (requireNamespace("vsn", quietly = TRUE)) {
  # vsn needs at least 42 features, so use 8 samples x 60 lipids
  m <- outer(1:8, 1:60, function(i, j) exp(6 + 0.05 * j + 0.3 * sin(i + j)))
  rownames(m) <- paste0("Sample_", seq_len(8))
  colnames(m) <- paste0("Lipid_", seq_len(60))
  dim(normalize_vsn(m))
}
```

perform_differential_analysis

Perform Differential Analysis

Description

Perform Differential Analysis

Usage

```
perform_differential_analysis(
  data_matrix,
  metadata,
  group_column = "Sample Group",
  contrasts_list = NULL,
  method = "limma",
  design = NULL
)
```

Arguments

<code>data_matrix</code>	Normalized data matrix (features as rows, samples as columns)
<code>metadata</code>	Metadata data frame. Must contain <code>group_column</code> and have a number of rows matching the samples in <code>data_matrix</code> .
<code>group_column</code>	Column name in metadata containing group information
<code>contrasts_list</code>	List of contrasts to perform
<code>method</code>	Method to use: "limma" or "edgeR"
<code>design</code>	Optional user-supplied design matrix (samples as rows). If NULL (the default), a design matrix of the form $\sim 0 + \text{group}$ is built automatically from <code>group_column</code> . When supplying a custom design, <code>contrasts_list</code> must also be supplied (limma/edgeR-style contrast strings referencing the design's column names).

Value

List containing results for each contrast

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
res <- perform_differential_analysis(norm, d$metadata, "Sample Group",
  contrasts_list = NULL, method = "limma"
)
names(res)
```

```
perform_enrichment_analysis
```

Perform Enrichment Analysis

Description

Perform Enrichment Analysis

Usage

```
perform_enrichment_analysis(
  results_list,
  classification_data,
  min_set_size = 5,
  max_set_size = 500,
  custom_sets = NULL
)
```

Arguments

`results_list` List of differential analysis results

`classification_data` Lipid classification data frame

`min_set_size` Minimum pathway set size

`max_set_size` Maximum pathway set size

`custom_sets` Optional named list of custom lipid sets

Value

List containing GSEA results

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
cls <- classify_lipids(colnames(norm))
res <- perform_differential_analysis(norm, d$metadata, "Sample Group",
  contrasts_list = NULL, method = "limma"
)
enrich <- perform_enrichment_analysis(res$results, cls, min_set_size = 3)
names(enrich)
```

perform_pca	<i>Perform PCA Analysis</i>
-------------	-----------------------------

Description

Perform PCA Analysis

Usage

```
perform_pca(data_matrix, metadata, group_column = "Sample Group")
```

Arguments

`data_matrix` Data matrix (samples as rows)

`metadata` Metadata data frame

`group_column` Group column name

Value

List containing PCA results and plot

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
pca_res <- perform_pca(norm, d$metadata, "Sample Group")
names(pca_res)
```

perform_plsda	<i>Perform PLS-DA Analysis</i>
---------------	--------------------------------

Description

Perform PLS-DA Analysis

Usage

```
perform_plsda(data_matrix, metadata, group_column = "Sample Group", n_comp = 2)
```

Arguments

data_matrix	Data matrix (samples as rows)
metadata	Metadata data frame
group_column	Group column name
n_comp	Number of components

Value

List containing PLS-DA results and plot

Examples

```
d <- load_lipidomics_data_from_df(generate_example_data())
norm <- apply_normalizations(d$numeric_data, c("TIC", "Log2"))
res <- perform_plsda(norm, d$metadata, "Sample Group")
names(res)
```

test_saturation_classification	
	<i>Test Saturation Classification</i>

Description

Convenience function to verify saturation detection on a set of lipid names.

Usage

```
test_saturation_classification(test_lipids = NULL)
```

Arguments

test_lipids	Optional character vector of lipid names to test. If NULL, a built-in test set is used.
-------------	---

Value

A data frame with columns Lipid and Saturation, printed to the console and returned invisibly.

Examples

```
test_saturation_classification()
```

visualize_raw_data	<i>Visualize Raw Data</i>
--------------------	---------------------------

Description

Produces a simple per-sample boxplot, density, or histogram of raw lipidomics intensities.

Usage

```
visualize_raw_data(data_list, plot_type = "boxplot")
```

Arguments

data_list	List as returned by <code>load_lipidomics_data</code> or <code>load_lipidomics_data_from_df</code> , must contain <code>\$numeric_data</code> .
plot_type	One of "boxplot", "density", or "histogram".

Value

A ggplot2 object.

Examples

```
d1 <- load_lipidomics_data_from_df(generate_example_data())
p <- visualize_raw_data(d1, "boxplot")
print(p)
```

`visualize_raw_data_improved`*Visualize Raw or Normalized Data with Sample/Lipid Toggle*

Description

Extended visualization that can show data from the sample perspective (one boxplot/violin/density per sample) or the lipid perspective (top variable lipids).

Usage

```
visualize_raw_data_improved(  
  data_list,  
  plot_type = "boxplot",  
  view_mode = "sample",  
  top_n = NULL,  
  metadata = NULL,  
  group_column = "Sample Group"  
)
```

Arguments

<code>data_list</code>	List with <code>\$numeric_data</code> (samples $\times$ lipids matrix).
<code>plot_type</code>	One of "boxplot", "violin", "density", or "histogram".
<code>view_mode</code>	Either "sample" or "lipid".
<code>top_n</code>	Integer or NULL. In lipid mode, the number of most variable lipids to display (defaults to 30 when NULL). In sample mode, the number of most variable samples to display; NULL (the default) shows all samples.
<code>metadata</code>	Optional metadata data frame (same row order as <code>numeric_data</code>) used to colour samples by group when <code>group_column</code> is provided.
<code>group_column</code>	Name of the group column in metadata.

Value

A `ggplot2` object.

Examples

```
d1 <- load_lipidomics_data_from_df(generate_example_data())  
p <- visualize_raw_data_improved(d1, "boxplot", "sample")  
print(p)
```

Index

* internal

LIPIDIFY-package, 3

apply_normalizations, 3, 5, 25

classify_lipids, 4

correct_batch_effects, 5

create_default_contrasts, 6

create_enrichment_barplot, 6

create_enrichment_dotplot, 7

create_heatmap_robust, 8

create_lipid_expression_barplot, 8

create_pca_plot_with_ellipses, 9

create_pipeline_plot, 10

create_plsda_plot_with_ellipses, 11

create_volcano_plot_labeled, 12

determine_saturation, 13

export_classification, 14

fix_sample_alignment, 14

generate_example_data, 15

get_imputation_descriptions, 15, 17

get_imputation_methods, 16

get_normalization_descriptions, 16

get_normalization_methods, 17

impute_missing_values, 17

launch_lipidomics_app, 3, 18

LIPIDIFY (LIPIDIFY-package), 3

LIPIDIFY-package, 3

load_custom_classification, 18

load_custom_enrichment_sets, 19

load_lipidomics_data, 20

load_lipidomics_data_from_df, 20

normalize_log2median, 4, 17, 21, 25

normalize_mean, 22

normalize_median, 22

normalize_pqn, 23

normalize_quantile, 23

normalize_tic, 24

normalize_vsn, 4, 17, 21, 22, 24

perform_differential_analysis, 25

perform_enrichment_analysis, 26

perform_pca, 27

perform_plsda, 28

removeBatchEffect, 5

test_saturation_classification, 29

visualize_raw_data, 29

visualize_raw_data_improved, 30