

Package ‘gVenn’

November 28, 2025

Title Proportional Venn and UpSet Diagrams for Gene Sets and Genomic Regions

Version 1.0.0

Description Tools to compute and visualize overlaps between gene sets or genomic regions. Venn diagrams with proportional areas are provided, while UpSet plots are recommended for larger numbers of sets. The package supports GRanges and GRangesList inputs, and integrates with analysis workflows for ChIP-seq, ATAC-seq, and other genomic interval data. It generates clean, interpretable, and publication-ready figures.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

URL <https://github.com/ckntav/gVenn>, <https://ckntav.github.io/gVenn/>

BugReports <https://github.com/ckntav/gVenn/issues>

Suggests testthat (>= 3.0.0), ggplot2, withr, knitr, rmarkdown

Config/testthat/edition 3

Imports ComplexHeatmap, eulerr, GenomicRanges, IRanges, lubridate, methods, rtracklayer, stringr, writexl

biocViews Software, Visualization, ChIPSeq, ATACSeq, Epigenetics, DataRepresentation, Sequencing

VignetteBuilder knitr

Depends R (>= 4.5.0)

LazyData false

git_url <https://git.bioconductor.org/packages/gVenn>

git_branch RELEASE_3_22

git_last_commit 27b5dfc

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2025-11-27

Author Christophe Tav [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-8808-9617>>)

Maintainer Christophe Tav <christophe.tav@gmail.com>

Contents

a549_chipseq_peaks	2
computeOverlaps	3
exportOverlaps	4
exportOverlapsToBed	5
extractOverlaps	6
gene_list	7
plotUpSet	7
plotVenn	8
saveViz	10
today	12
Index	13

a549_chipseq_peaks	<i>A549 ChIP-seq Consensus Peak Subsets (Dex, chr7)</i>
--------------------	---

Description

Example consensus peak subsets for MED1, BRD4, and GR after dexamethasone treatment in A549 cells. Each set has been restricted to peaks on chr7 to keep the dataset small and suitable for examples and tests.

Usage

a549_chipseq_peaks

Format

- A GRangesList with 3 named elements:
- MED1_Dex_chr7** Consensus MED1 peaks (chr7 subset).
 - BRD4_Dex_chr7** Consensus BRD4 peaks (chr7 subset).
 - GR_Dex_chr7** Consensus GR peaks (chr7 subset).

Details

The original full consensus peak sets are available as gzipped BED files in inst/extdata/:

- A549_MED1_Dex.stdchr.bed.gz
- A549_BRD4_Dex.stdchr.bed.gz
- A549_GR_Dex.stdchr.bed.gz

These are not trimmed, but for package efficiency the dataset here (a549_chipseq_peaks) only includes the chr7 subsets.

Source

Internal consensus peak sets processed in A549 cells after dexamethasone stimulation.

References

Tav C, Fournier É, Fournier M, Khadangi F, Baguette A, Côté MC, Silveira MAD, Bérubé-Simard F-A, Bourque G, Droit A, Bilodeau S (2023). "Glucocorticoid stimulation induces regionalized gene responses within topologically associating domains." *Frontiers in Genetics*. doi:10.3389/fgene.2023.1237092

Examples

```
# Load dataset
data(a549_chipseq_peaks)
a549_chipseq_peaks

# Compute overlaps and plot
ov <- computeOverlaps(a549_chipseq_peaks)
plotVenn(ov)
```

computeOverlaps

Compute Overlaps Between Multiple Sets or Genomic Regions

Description

computeOverlaps() is the main entry point for overlap analysis. It accepts either genomic region objects (GRanges/GRangesList) or ordinary sets (character/numeric vectors) and computes a binary overlap matrix describing the presence or absence of each element across sets.

Usage

```
computeOverlaps(x)
```

Arguments

x Input sets. One of:

- A GRangesList object.
- A named list of GRanges objects.
- A named list of atomic vectors (character, numeric, factor, etc.), all of the same type.

Details

- When provided with genomic regions, the function merges all intervals into a non-redundant set (reduce()), then determines which original sets each region overlaps.
- When provided with ordinary sets (e.g., gene symbols), it collects all unique elements and records which sets contain them.

The resulting object encodes both the overlap matrix and compact category labels (e.g., "110") representing the overlap pattern of each element. These results can be directly passed to visualization functions such as plotVenn() or plotUpSet().

Internally, computeOverlaps() dispatches to either computeGenomicOverlaps() (for genomic inputs) or computeSetOverlaps() (for ordinary sets). Users are encouraged to call only computeOverlaps().

Value

An S3 object encoding the overlap result whose class depends on the input type:

GenomicOverlapResult Returned when the input is genomic (GRangesList or list of GRanges).

A list with:

- **reduced_regions**: A GRanges object containing the merged (non-redundant) intervals. Each region is annotated with an **intersect_category** column.
- **overlap_matrix**: A logical matrix indicating whether each reduced region overlaps each input set (rows = regions, columns = sets).

SetOverlapResult Returned when the input is a list of atomic vectors. A list with:

- **unique_elements**: Character vector of all unique elements across the sets.
- **overlap_matrix**: A logical matrix indicating whether each element is present in each set (rows = elements, columns = sets).
- **intersect_category**: Character vector of category codes (e.g., "110") for each element.

See Also

[plotVenn](#), [plotUpSet](#), [GRangesList](#), [reduce](#)

Examples

```
# Example with gene sets (built-in dataset)
data(gene_list)
ov_sets <- computeOverlaps(gene_list)
head(ov_sets$overlap_matrix)
plotVenn(ov_sets)

# Example with genomic regions (built-in dataset)
data(a549_chipseq_peaks)
ov_gr <- computeOverlaps(a549_chipseq_peaks)
head(ov_gr$overlap_matrix)
plotVenn(ov_gr)
```

exportOverlaps

Export Overlap Groups to Excel

Description

This function exports the output of `extractOverlaps()` to an Excel file, creating one sheet per overlap group. Genomic overlaps (GRanges) are converted to data frames before export.

Usage

```
exportOverlaps(
  grouped,
  output_dir = ".",
  output_file = "overlap_groups",
  with_date = TRUE,
  verbose = TRUE
)
```

Arguments

grouped	Overlap groups from <code>extractOverlaps()</code> .
output_dir	A string specifying the output directory. Defaults to ".".
output_file	A string specifying the base filename (without extension). Defaults to "overlap_groups".
with_date	Logical (default TRUE). Whether to prepend the current date (from today) to the filename.
verbose	Logical. If TRUE, print a message with the saved path. Default TRUE.

Value

Overlap groups are saved to a Excel file on disk. Invisibly returns the full path to the saved file.

Examples

```
res <- computeOverlaps(list(A = letters[1:3], B = letters[2:4]))
grouped <- extractOverlaps(res)
exportOverlaps(grouped, output_dir = tempdir(), output_file = "overlap_groups")
```

exportOverlapsToBed	<i>Export Overlap Groups to BED Files</i>
---------------------	---

Description

This function exports genomic overlap groups from `extractOverlaps()` to BED format files, creating one BED file per overlap group.

Usage

```
exportOverlapsToBed(
  grouped,
  output_dir = ".",
  output_prefix = "overlaps",
  with_date = TRUE,
  verbose = TRUE
)
```

Arguments

grouped	Genomic overlap groups from <code>extractOverlaps()</code> (must be <code>GRangesList</code>).
output_dir	A string specifying the output directory. Defaults to ".".
output_prefix	A string specifying the filename prefix. Defaults to "overlaps".
with_date	Logical (default TRUE). Whether to prepend the current date to filenames.
verbose	Logical. If TRUE, print messages. Default TRUE.

Details

This function only works with genomic overlaps (i.e., when the input to `extractOverlaps()` was a `GenomicOverlapResult` object, resulting in a `GRangesList`). It does not work with set overlaps (character vectors). Each overlap group will be saved as a separate BED file with the group identifier included in the filename.

Value

Invisibly returns a character vector of file paths created.

`extractOverlaps`*Extract Overlap Groups from Genomic or Set Overlap Results*

Description

This function extracts subsets of intersecting elements grouped by their overlap category (e.g., "110"). For genomic overlaps, it returns a `GRangesList`; for set overlaps, it returns a named list of character vectors.

Usage

```
extractOverlaps(overlap_object)
```

Arguments

`overlap_object` A `GenomicOverlapsResult` or `SetOverlapsResult` object.

Value

A named list of grouped intersecting elements:

- If input is a `GenomicOverlapsResult`, a `GRangesList` split by `intersect_category`.
- If input is a `SetOverlapsResult`, a named list of character vectors grouped by `intersect_category`.

Examples

```
# Example with gene sets (built-in dataset)
data(gene_list)
res_sets <- computeOverlaps(gene_list)
group_gene <- extractOverlaps(res_sets)
group_gene

# Example with genomic regions (built-in dataset)
data(a549_chipseq_peaks)
res_genomic <- computeOverlaps(a549_chipseq_peaks)
group_genomic <- extractOverlaps(res_genomic)
group_genomic
```

gene_list*Example Gene Lists with Overlaps*

Description

A synthetic dataset of three gene lists, created from the first 250 human gene symbols in **org.Hs.eg.db**.

Usage

```
gene_list
```

Format

A named list of length 3. Each element is a character vector of gene symbols:

random_genes_A 125 gene symbols.

random_genes_B 115 gene symbols.

random_genes_C 70 gene symbols.

Source

Generated from **org.Hs.eg.db** (keys of type SYMBOL), using a reproducible random seed.

Examples

```
data(gene_list)

# Inspect the list
str(gene_list)

# Compute overlaps and plot
ov <- computeOverlaps(gene_list)
plotVenn(ov)
```

plotUpSet*Plot an UpSet Diagram from Genomic or Set Overlap Results*

Description

This function creates an UpSet plot using the ComplexHeatmap package to visualize intersections across multiple sets. Supports both GenomicOverlapsResult and SetOverlapsResult objects.

Usage

```
plotUpSet(overlap_object, customSetOrder = NULL, comb_col = "black")
```

Arguments

- overlap_object A GenomicOverlapsResult or SetOverlapsResult object returned by [computeOverlaps](#).
- customSetOrder Optional. A vector specifying the order of sets to display on the UpSet diagram. The vector should contain either numeric indices (corresponding to the sets in the overlap object) or character names (matching the set names). If NULL (default), sets are displayed in decreasing order of their size (`set_size()`).
- comb_col Optional. Color(s) for the combination matrix dots and connecting lines. Can be a single color, a vector of colors (recycled to match the number of intersections). Default is "black".

Value

An UpSet plot object generated by `ComplexHeatmap::UpSet`.

Examples

```
# Example with gene sets (built-in dataset)
data(gene_list)
res_sets <- computeOverlaps(gene_list)

# Default order (sets sorted by size)
plotUpSet(res_sets)

# Custom color
plotUpSet(res_sets, comb_col = "darkblue")

# Custom order by names
plotUpSet(res_sets, customSetOrder = c("random_genes_C",
                                       "random_genes_A",
                                       "random_genes_B"))

# Example with genomic regions (built-in dataset)
data(a549_chipseq_peaks)
res_genomic <- computeOverlaps(a549_chipseq_peaks)
plotUpSet(res_genomic)
```

plotVenn

Plot a Venn Diagram from Genomic or Set Overlap Results

Description

This function creates a Venn diagram using the `eulerr` package to visualize intersections across multiple sets. Supports both `GenomicOverlapsResult` and `SetOverlapsResult` objects.

Usage

```
plotVenn(
  overlap_object,
  fills = TRUE,
  edges = TRUE,
  labels = FALSE,
  quantities = list(type = "counts"),
```



```

    legend = "right",
    main = NULL,
    ...
)

```

Arguments

overlap_object	A GenomicOverlapsResult or SetOverlapsResult object returned by computeOverlaps .
fills	Controls the fill appearance of the diagram. Can be: • logical: TRUE (default) shows fills, FALSE hides them • character vector: Colors for the fills. Default colors are: c("#2B70AB", "#FFB027", "#3EA742", "#CD3301", "#9370DB", "#008B8B", "#D87093") • list: Fine control with graphical parameters including fill (colors), alpha (transparency 0-1)
edges	Controls the edge/border appearance. Can be: • logical: TRUE (default) shows edges, FALSE hides them • character vector: Colors for the edges • list: Fine control with col (colors), alpha (transparency 0-1), lty (line type), lwd (line width), lex (line expansion)
labels	Controls set labels. Can be: • logical: TRUE shows default labels, FALSE hides them • character vector: Custom text for labels • list: Fine control with col (text color), fontsize, font (1=plain, 2=bold, 3=italic, 4=bold italic), fontfamily, cex (character expansion), alpha (transparency 0-1)
quantities	Controls intersection quantities display. Can be: • logical: TRUE shows counts, FALSE hides them • character vector: Custom text labels • list: Fine control with type (c("counts", "percent")), col (text color), fontsize, font, fontfamily, cex, alpha
legend	Controls the legend. Can be: • logical: FALSE to disable • character: Position ("right", "top", "bottom", "left") • list: Fine control with side (position), labels (custom labels), col, fontsize, cex, fontfamily
main	Title for the plot. Can be character, expression, or list with label (text), col, fontsize, font, fontfamily
...	Additional arguments passed to plot.euler .

Value

A Venn diagram plot generated by `eulerr`.

Examples

```
# Example with gene sets
data(gene_list)
res_sets <- computeOverlaps(gene_list)

# Basic plot
plotVenn(res_sets)

# Customize fills with transparency and custom colors
plotVenn(res_sets,
  fills = list(fill = c("#FF6B6B", "#4ECDC4", "#45B7D1"),
    alpha = 0.6))

# Customize edges
plotVenn(res_sets,
  edges = list(col = "darkgray", lwd = 2, lty = 2))

# Customize labels
plotVenn(res_sets,
  labels = list(col = "white", font = 2, fontsize = 14))

# Show both counts and percentages
plotVenn(res_sets,
  quantities = list(type = c("counts", "percent"),
    col = "black", fontsize = 10))

# Add a title
plotVenn(res_sets,
  main = list(label = "Gene Set Overlaps",
    col = "navy", fontsize = 16, font = 2))

# Transparent fills with colored borders only
plotVenn(res_sets,
  fills = "transparent",
  edges = list(col = c("red", "blue", "green"), lwd = 3))

# Custom legend
plotVenn(res_sets,
  legend = list(side = "bottom",
    labels = c("Treatment A", "Treatment B", "Control"),
    fontsize = 12))
```

saveViz

Save a Visualization to File (PDF, PNG, or SVG)

Description

This function saves a visualization object to a file in the specified format and directory. It supports visualizations generated by `plotVenn()`, `plotUpSet()`, `ggplot2`, or any other plot object that can be rendered using `print()` inside a graphics device. Optionally, the current date (stored in the `today` variable) can be prepended to the filename.

Usage

```
saveViz(
  viz,
  output_dir = ".",
  output_file = "figure_gVenn",
  format = "pdf",
  with_date = TRUE,
  width = 5,
  height = 5,
  resolution = 300,
  verbose = TRUE
)
```

Arguments

<code>viz</code>	A visualization object typically created by either <code>plotVenn()</code> or <code>plotUpSet()</code> , but can also be a <code>ggplot2</code> plot or any other plot object printable with <code>print()</code> .
<code>output_dir</code>	A string specifying the output directory. Defaults to ".".
<code>output_file</code>	A string specifying the base filename (without extension). Defaults to "viz_genomicVenn".
<code>format</code>	Output format. One of "pdf", "png", or "svg". Defaults to "pdf".
<code>with_date</code>	Logical (default TRUE). Whether to prepend the current date (from today) to the filename.
<code>width</code>	Width of the output file in inches. Default is 5.
<code>height</code>	Height of the output file in inches. Default is 5.
<code>resolution</code>	Resolution in DPI (only used for PNG). Default is 300.
<code>verbose</code>	Logical. If TRUE, print a message with the saved path. Default TRUE.

Value

The visualization is saved to a file on disk. Invisibly returns the full path to the saved file.

Examples

```
# Example with a built-in set dataset
data(gene_list)
ov_sets <- computeOverlaps(gene_list)
venn_plot <- plotVenn(ov_sets)
saveViz(venn_plot, output_dir = tempdir(), output_file = "venn_sets")

# Example with a built-in genomic dataset
data(a549_chipseq_peaks)
ov_genomic <- computeOverlaps(a549_chipseq_peaks)
upset_plot <- plotUpSet(ov_genomic)
saveViz(upset_plot, output_dir = tempdir(), output_file = "upset_genomic")

# Save as PNG instead of PDF
saveViz(upset_plot, format = "png", output_dir = tempdir(), output_file = "upset_example")

# Save as SVG
saveViz(venn_plot, format = "svg", output_dir = tempdir(), output_file = "venn_example")
```

today

Today's Date at Package Load Time

Description

This variable stores the current date (in "yyyymmdd" format) at the time the package is loaded. It is useful for reproducible filenames (e.g., in `saveViz()`), and is automatically set when the package is attached.

Usage

today

Format

A character string (e.g., "20250624").

Examples

```
# Print the date stored at package load
library(gVenn)
today

# Use it in a filename
paste0("venn_plot_", today, ".pdf")
```

Index

* datasets

a549_chipseq_peaks, [2](#)

gene_list, [7](#)

today, [12](#)

a549_chipseq_peaks, [2](#)

computeOverlaps, [3](#), [8](#), [9](#)

exportOverlaps, [4](#)

exportOverlapsToBed, [5](#)

extractOverlaps, [6](#)

gene_list, [7](#)

GRangesList, [4](#)

plot.euler, [9](#)

plotUpSet, [4](#), [7](#)

plotVenn, [4](#), [8](#)

reduce, [4](#)

saveViz, [10](#)

today, [12](#)